



zandleven coatings

Corrosie classificatie volgens ISO 12944-5

Beschermingsduur	Systeemnr.	Type	Product	laagdikte
C4	Thermisch verzinkt staal			
5 - 15 jaar	1	EP	Monopox ZF Universal	80 µm
		PUR	Polyfinish HS	80 µm
			Totaal	160 µm
	2	EP	Monopox Metalsealer	80 µm
PUR		Polyfinish Ijzerglimmer HB	80 µm	
		Totaal	160 µm	
> 15 jaar	1	EP	Monopox ZF-Universal	80 µm
		EP	Monopox HB Coating	80 µm
		PUR	Polyfinish HS	80 µm
			Totaal	240 µm

De hierboven vermelde systemen zijn voorbeeldsystemen. In veel gevallen wordt er gevraagd om specifieke eisen door een opdrachtgever en/of applicateur. Voor een op maat gemaakt advies kunt u zich wenden tot onze technische afdeling.

Versiedatum: 3-5-2016



All our offers, contracts, deliveries, services and all correspondence, including email, are subject to the General Terms and Conditions of Delivery from the branch organisation of the Paint Printing Ink Industry (VVFV) of 2003 which are deposited at the office of the Clerk of the District Court of Amsterdam; number and date on request. They are an integral part of all contracts that we conclude with our contractual partners for the deliveries and services we offer. Of the Uniform Sales conditions deviating purchasing conditions of the buyer will not be accepted by us. See Article 1 of the Uniform Sales conditions on www.zandleven.com

