




zandleven coatings

Corrosion classification according ISO 12944-5:2018

Durability	System no.	Type	Product	DFT
C4			Hot dip galvanised steel	
			Thermal spray metallic	
7 - 15 years	1	EP	Monopox ZF Universal	80 m
		PUR	Polyfinish HS	80 m
			Total	160 m
	2	EP	Monopox Metalsealer	80 m
		PUR	Polyfinish Ijzerglimmer HB	0 m
			Total	160 m
15 - 25 years	1	EP	Monopox ZF-Universal	70 m
		EP	Monopox HB Coating	70 m
		PUR	Polyfinish HS	60 m
			Total	200 m
>25 years	1	EP	Monopox ZF-Universal	80 m
		EP	Monopox HB Coating	80 m
		PUR	Polyfinish HS	80 m
			Total	240 m

The systems mentioned above are example systems. In many cases there is asked for specific demands by an contracting party and/or applicator. Please contact our technical department for a tailor made advice.

Validation date: 2-7-2018



All our offers, contracts, deliveries, services and all correspondence, including email, are subject to the General Terms and Conditions of Delivery from the branch organisation of the Paint Printing ink Industry (VVFV) of 2003 which are deposited at the office of the Clerk of the District Court of Amsterdam; number and date on request. They are an integral part of all contracts that we conclude with our contractual partners for the deliveries and services we offer. Of the Uniform Sales conditions deviating purchasing conditions of the buyer will not be accepted by us. See Article 1 of the Uniform Sales conditions on www.zandleven.com

