



# zandleven coatings

Corrosion classification according ISO 12944-5:2018

Durability	System no.	Type	Product	DFT
<b>C5</b>	<b>Hot dip galvanised steel</b>			
	<b>Thermal spray metallic</b>			
1 - 7 years	1	EP	Monopox ZF Universal	80 µm
		PUR	Polyfinish HS	80 µm
		Total		160 µm
	2	EP	Monopox Metalsealer	80 µm
		PUR	Polyfinish Ijzerglimmer HB	80 µm
		Total		160 µm
7 - 15 years	1	EP	Monopox ZF-Universal	80 µm
		EP	Monopox HB Coating	80 µm
		PUR	Polyfinish HS	80 µm
	Total		240 µm	
	2	EP	Monopox Metalsealer	80 µm
		EP	Monopox HB Ijzerglimmer	80 µm
PUR		Polyfinish HS	80 µm	
Total		240 µm		
15 – 25 years	1	EP	Monopox ZF-Universal	80 µm
		EP	Monopox HS-U	160 µm
		PUR	Polyfinish HS	80 µm
		Total		320 µm

The systems mentioned above are example systems. In many cases there is asked for specific demands by an contracting party and/or applicator. Please contact our technical department for a tailor made advice.

Validation date: 2-7-2018



All our offers, contracts, deliveries, services and all correspondence, including email, are subject to the General Terms and Conditions of Delivery from the branch organisation of the Paint Printing Ink Industry (VVFV) of 2003 which are deposited at the office of the Clerk of the District Court of Amsterdam; number and date on request. They are an integral part of all contracts that we conclude with our contractual partners for the deliveries and services we offer. Of the Uniform Sales conditions deviating purchasing conditions of the buyer will not be accepted by us. See Article 1 of the Uniform Sales conditions on [www.zandleven.com](http://www.zandleven.com)

