



Printing date 06.02.2025 Version: 35 (replaces version 34) Revision: 06.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name: 2 V 4 VERHARDER WINTERCURE

· Article number: 2V4-WINTER · UFI: 4HXA-Q1SK-P00X-W5JS

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC7 Industrial spraying

PROC10 Roller application or brushing

PROC19 Manual activities involving hand contact PROC13 Treatment of articles by dipping and pouring

· Application of the substance / the mixture solvent based, two component epoxy coating hardener

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Zandleven Coatings B.V.

Snekertrekweg 57-59, 8912 AA Leeuwarden, Netherlands

Tel: +31 58 2129545 Fax: +31 58 2155996

E-mail: info@zandleven.com Internet: www.zandleven.com

· Further information obtainable from: R&D department: sds@zandleven.com

· 1.4 Emergency telephone number:

Nationaal Vergiftigingen Informatie

+31 (0)88 755 8000

ORFILA (INRS): + 33 (0)1 45 42 59 59 Centres Antipoison et de Toxicovigilance

ANGERS: 02 41 48 21 21 BORDEAUX: 05 56 96 40 80 LILLE: 0800 59 59 59 LYON: 04 72 11 69 11 MARSEILLE: 04 91 75 25 25 NANCY: 03 83 22 50 50 PARIS: 01 40 05 48 48 STRASBOURG: 03 88 37 37 37

TOULOUSE: 05 61 77 74 47

Giftnotruf der Charité, Berlin: 030/19240

Giftinformationszentrum-Nord der Länder Bremen, Hamburg, Niedersachsen und Schleswig-Holstein (GIZ-

Nord):0551/19 240

Informationszentrale gegen Vergiftungen Zentrum für Kinderheilkunde Universitätsklinikum Bonn: 0228/19240 Giftnotruf Erfurt Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen,

Sachsen-Anhalt und Thüringen: 0361/730 730

Informations- und Beratungszentrum für Vergiftungsfälle Klinik für Kinder- und Jugendmedizin

Universitätsklinikum des Saarlandes: 06841/19240

Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen - Klinische Toxikologie - Universitätsmedizin der Johannes Gutenberg-Universität Mainz: 06131/19240

Vergiftungs-Informations-Zentrale Zentrum für Kinder- und Jugendmedizin Universitätsklinikum: 0761/19240 Giftnotruf München Toxikologische Abteilung der II. Med. Klinik und Poliklinik: 089/19240

+31 (0)58 2677590 (during office hours)

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.

(Contd. on page 2)





Printing date 06.02.2025 Version: 35 (replaces version 34) Revision: 06.02.2025

Trade name: 2 V 4 VERHARDER WINTERCURE

(Contd. of page 1)

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms





GHS02 GHS05

- Signal word Danger
- · Hazard-determining components of labelling:

butan-1-ol

· Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smokina.

P303+P361+P353 IF ON ŠKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 F IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- PBT: Not applicable.vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- Description: Mixture of substances listed below with nonhazardous additions.
- · Dangerous components:

Percentages of the components are expressed as a percentage by weight

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226; Sasp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 02-2119484630-38	butan-1-ol Flam. Liq. 3, H226;	10-25%
CAS: 90-72-2 EINECS: 202-013-9 Index number: 603-069-00-0 Reg.nr.: 01-2119560597-27	2,4,6-tris(dimethylaminomethyl)phenol Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319	2.5-10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	2.5-10%

Additional information: For the wording of the listed hazard phrases refer to section 16.

EU ·





Printing date 06.02.2025 Version: 35 (replaces version 34) Revision: 06.02.2025

Trade name: 2 V 4 VERHARDER WINTERCURE

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- · 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

· 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- \cdot Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store material in original, well-closed packages in a cool, well-ventilated area according to local regulations.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 30 °C
- · 7.3 Specific end use(s) No further relevant information available.

-EU





Printing date 06.02.2025 Version: 35 (replaces version 34) Revision: 06.02.2025

Trade name: 2 V 4 VERHARDER WINTERCURE

(Contd. of page 3)

8.1 Contr	ol parameters		
	ts with limit values that require mo	nitoring at t	he worknlace:
1330-20-7	-	intorning at t	ne workplace.
	nort-term value: 442 mg/m³, 100 ppm		
Lo	ng-term value: 221 mg/m³, 50 ppm		
Sk			
	ethylbenzene		
	nort-term value: 884 mg/m³, 200 ppm ong-term value: 442 mg/m³, 100 ppm		
Sk			
DNEL (De	rived No Effect Level) for workers:		
1330-20-7	-		
Dermal	Long-term - systemic effects, worker	212 mg/kg	bw/day (worker)
Inhalative	Acute - systemic effects, worker	442 mg/m³	· , , , , , , , , , , , , , , , , , , ,
	Acute - local effects, worker	442 mg/m³	(worker)
	Long-term - systemic effects, worker	_	
	Long-term - local effects, worker	221 mg/m³	· · · ·
71-36-3 bi	utan-1-ol		
Inhalative	Long-term - local effects, worker	310 mg/m ³	(worker)
90-72-2 2,	4,6-tris(dimethylaminomethyl)phen	ol	
Dermal	Acute - systemic effects, worker	0.6 mg/kg l	ow/day (worker)
	Long-term - systemic effects, worker	0.15 mg/kg	bw/day (worker)
Inhalative	Acute - systemic effects, worker	2.1 mg/m ³ (` ,
	Long-term - systemic effects, worker	0.53 mg/m ³	³ (worker)
	ethylbenzene		
Dermal	Long-term - systemic effects, worker		· , ,
Inhalative	Acute - local effects, worker	293 mg/m ³	•
	Long-term - systemic effects, worker	77 mg/m³ (worker)
DNEL (De	rived No Effect Level) for the gener	al polulatio	n:
1330-20-7	-		
Oral	1		12.5 mg/kg bw/day (general population)
Dermal	Long-term - systemic effects, general		125 mg/kg bw/day (general population)
Inhalative	Acute - systemic effects, general pop		260 mg/m³ (general population)
	Acute - local effects, general populati		260 mg/m³ (general population)
	Long-term - systemic effects, general		- 1- 1
	Long-term - local effects, general por	oulation	65.3 mg/m³ (general population)
71-36-3 bi			
Oral	1		3.125 mg/kg bw/day (general population)
	Long-term - local effects, general por		55 mg/m³ (general population)
	4,6-tris(dimethylaminomethyl)phen		0.075
Oral			0.075 mg/kg bw/day (general population)
Dermal	Acute - systemic effects, general poli		0.075 mg/kg bw/day (general population)
Inheletive	Long-term - systemic effects, general		0.075 mg/kg bw/day (general population)
ıımaıatıve	Acute - systemic effects, general pop		0.13 mg/m³ (general population)
100 11 1	Long-term - systemic effects, general	population	U. 13 mg/m² (general population)
100-41-4 (Oral	ethylbenzene	l nonulation	1.6 malka bulday (saparal namilation)
UIAI	i Long-leitii - syslemic ettecis. denera	i population	1.6 mg/kg bw/day (general population)



Printing date 06.02.2025 Version: 35 (replaces version 34) Revision: 06.02.2025

Trade name: 2 V 4 VERHARDER WINTERCURE

	(Contd. of pag
PNEC (Predicted No Effect Concentration) value	es:
1330-20-7 xylene	
Aquatic compartment - freshwater	0.327 mg/L (freshwater)
Aquatic compartment - marine water	0.327 mg/L (marine water)
Aquatic compartment - water, intermittent releases	0.327 mg/L (intermittent release water)
Aquatic compartment - sediment in freshwater	12.46 mg/kg sed dw (sediment fresh water)
Aquatic compartment - sediment in marine water	12.46 mg/kg sed dw (sediment marine water)
Terrestrial compartment - soil	2.31 mg/kg dw (soil)
Sewage treatment plant	6.58 mg/L (sewage treatment plant)
71-36-3 butan-1-ol	
Aquatic compartment - freshwater	0.082 mg/L (not specified)
Aquatic compartment - marine water	0.0082 mg/L (not specified)
Aquatic compartment - water, intermittent releases	2.25 mg/L (not specified)
Aquatic compartment - sediment in freshwater	0.178 mg/kg sed dw (not specified)
Aquatic compartment - sediment in marine water	0.0178 mg/kg sed dw (not specified)
Terrestrial compartment - soil	0.015 mg/kg dw (not specified)
Sewage treatment plant	2,476 mg/L (not specified)
90-72-2 2,4,6-tris(dimethylaminomethyl)phenol	
Aquatic compartment - freshwater	0.046 mg/L (freshwater)
Aquatic compartment - marine water	0.005 mg/L (marine water)
Aquatic compartment - water, intermittent releases	0.46 mg/L (intermittent release water)
Aquatic compartment - sediment in freshwater	0.262 mg/kg sed dw (sediment fresh water)
Aquatic compartment - sediment in marine water	0.025 mg/kg sed dw (sediment marine water)
Terrestrial compartment - soil	0.025 mg/kg dw (soil)
Sewage treatment plant	0.2 mg/L (sewage treatment plant)
100-41-4 ethylbenzene	
Aquatic compartment - freshwater	0.1 mg/L (not specified)
Aquatic compartment - marine water	0.01 mg/L (not specified)
Aquatic compartment - water, intermittent releases	0.1 mg/L (not specified)
Aquatic compartment - sediment in freshwater	13.7 mg/kg sed dw (not specified)
Aquatic compartment - sediment in marine water	1.37 mg/kg sed dw (not specified)
Terrestrial compartment - soil	2.68 mg/kg dw (not specified)
Sewage treatment plant	9.6 mg/L (not specified)
Oral secondary poisoning	0.02 mg/kg food (not specified)

Additional information: The lists valid during the making were used as basis.

· 8.2 Exposure controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne

contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

- · Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Provide readily accessible eye wash stations and safety showers.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

Respiratory protection:

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If

workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed

respirator complying with an approved standard if a risk assessment indicates this is necessary.

(Contd. on page 6)





Printing date 06.02.2025 Version: 35 (replaces version 34) Revision: 06.02.2025

Trade name: 2 V 4 VERHARDER WINTERCURE

(Contd. of page 5)

For organic vapors and solvents type of filter A1 or A2, for dust type of filter P (according to EN 140)

· Hand protection



Protective gloves

Chemical resistant gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

Penetration time of glove material

KCL Vitoject 890

breakthrough time > 480 min.

thickness: 0,7 mm

at limited contact

KCL Camatril 730

breakthrough time 30 min.

thickness: 0,4 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed

- · Not suitable are gloves made of the following materials: All other materials
- Eye/face protection



Tightly sealed goggles

Safety glasses according to EN 166 or equivalent

· Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved before the product is used by a specialist.

If there is a risk of ignition by static electricity, anti-static protective clothing should be worn. For the best protection against static discharge, clothing should consist of anti-static overalls, boots and gloves. For further information on materials and design requirements and test methods consult the European standard EN 1149.

· Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

- · 9.1 Information on basic physical and chemical properties
- · General Information

· Physical state Liquid

Boiling point or initial boiling point and boiling

Colour: According to product specification

Odour: Characteristic

Odour threshold: Not determined.Melting point/freezing point: Undetermined.

range 116-118 °C (71-36-3 butan-1-ol)

(Contd. on page 7)



Printing date 06.02.2025 Version: 35 (replaces version 34) Revision: 06.02.2025

Trade name: 2 V 4 VERHARDER WINTERCURE

(Contd. of page 6)

· **Flammability** Flammable.

· Lower and upper explosion limit

• **Lower:** 1.1 Vol % (1330-20-7 xylene) • **Upper:** 9.4 Vol % (71-36-3 butan-1-ol)

· Flash point: 30 °C

• **Auto-ignition temperature:** 340 °C (71-36-3 butan-1-ol)

Decomposition temperature: Not determined.

· **pH at 20 °C** 10

· Viscosity:

• Kinematic viscosity at 40 °C: > 20,5 mm²/s

· **Dynamic at 20 °C:** 500 mPas

· Solubility

• water: Fully miscible.
• Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 10 hPa (71-36-3 butan-1-ol)

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density
 Not determined.
 Not determined.

9.2 Other information

· Appearance:

· Form: Fluid

Important information on protection of health and environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Change in condition

• Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void
Flammable gases Void
Aerosols Void
Oxidising gases Void
Gases under pressure Void

• Flammable liquids Flammable liquid and vapour.

Flammable solids
 Self-reactive substances and mixtures
 Pyrophoric liquids
 Pyrophoric solids
 Self-heating substances and mixtures
 Substances and mixtures

Substances and mixtures, which emit flammable gases in contact with water
 Oxidising liquids
 Oxidising solids
 Organic peroxides
 Corrosive to metals
 Desensitised explosives

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.

(Contd. on page 8)





Printing date 06.02.2025 Version: 35 (replaces version 34) Revision: 06.02.2025

Trade name: 2 V 4 VERHARDER WINTERCURE

(Contd. of page 7)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 \	· LD/LC50 values relevant for classification:			
1330-20-7	1330-20-7 xylene			
Oral	LD50	3,523 mg/kg (rat)		
Dermal	LD50	2,000 mg/kg (rabbit)		
71-36-3 bu	71-36-3 butan-1-ol			
Oral	LD50	790 mg/kg (rat)		
Dermal	LD50	3,400 mg/kg (rabbit)		
Inhalative	LC50/4 h	8,000 mg/l (rat)		
90-72-2 2,	90-72-2 2,4,6-tris(dimethylaminomethyl)phenol			
Oral	LD50	2,169 mg/kg (rat)		
100-41-4 €	100-41-4 ethylbenzene			
Oral	LD50	3,500 mg/kg (rat)		
Dermal	LD50	17,800 mg/kg (rabbit)		

- Primary irritant effect:
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye damage.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

12.1 TOXICITY			
· Aquatic toxicity:			
1330-20-7 xylene			
EC50/72 h	2.2 mg/l (algae)		
EC50/48 h	>3.4 mg/l (Ceriodaphnia dubia)		
LC50/96 h	LC50/96 h 2.6 mg/l (Oncorhynchus mykiss)		
LC50/24 h	LC50/24 h 1 mg/l (Daphnia magna)		
71-36-3 bu	71-36-3 butan-1-ol		
EC50/48 h	1,328 mg/l (Daphnia magna)		
LC50/96 h	1,376 mg/l (pimephales promelas)		
90-72-2 2,4	90-72-2 2,4,6-tris(dimethylaminomethyl)phenol		
EC50/96 h	718 mg/l (Palaemonetes vulgaris (grass shrimp))		
EC50/72 h	84 mg/l (algae)		
LC50/96 h	175 mg/l (Cyprinus carpio)		
LC50/24 h	249 mg/l (Cyprinus carpio)		
	222 mg/l (Oncorhynchus mykiss)		
	(Contd. on page 0)		

(Contd. on page 9)





Printing date 06.02.2025 Version: 35 (replaces version 34) Revision: 06.02.2025

Trade name: 2 V 4 VERHARDER WINTERCURE

(Contd. of page 8)

| 100-41-4 ethylbenzene | EC50/72 h | 3.6-4.2 mg/l (algae) | EC50/24 h | 2.2 mg/l (Daphnia magna) | LC50/96 h | 4.2 mg/l (Oncorhynchus mykiss)

- · 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue		
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS	
08 01 00	wastes from MFSU and removal of paint and varnish	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
HP3	HP3 Flammable	
HP4	HP4 Irritant - skin irritation and eye damage	
HP6	Acute Toxicity	

- · Uncleaned packaging:
- **Recommendation**: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information

Transport in accordance with ADR/RID, IMDG and ICAO/IATA.

· 14.1 UN number or ID number · ADR/RID/ADN, ADN, IMDG · IATA	Void UN1263
· 14.2 UN proper shipping name · ADR/RID/ADN, ADN, IMDG · IATA	Void PAINT

(Contd. on page 10)

Page 10/11



Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.02.2025 Version: 35 (replaces version 34) Revision: 06.02.2025

Trade name: 2 V 4 VERHARDER WINTERCURE

	(Contd. of page
14.3 Transport hazard class(es)	
ADR/RID/ADN, ADN, IMDG	
Class	Void
IATA	
Class	3 Flammable liquids.
Label	3
14.4 Packing group	
ADR/RID/ADN, IMDG	Void
IATA	III
14.5 Environmental hazards:	
Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according	g to IMO
instruments	Not applicable.
Transport/Additional information:	
ADR/RID/ADN	
Remarks:	Up to 450 litre exempted according to ADR 2.2.3.1.5.
IMDG	
Remarks:	Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code.
IATA	
Remarks:	The "viscosity exemption" provisions do NOT apply to a transport.
UN "Model Regulation":	Void

SECTION 15: Regulatory information

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- $^{\circ}$ Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

- REGULATION (EU) 2019/1148
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

· Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

(Contd. on page 11)





Printing date 06.02.2025 Version: 35 (replaces version 34) Revision: 06.02.2025

Trade name: 2 V 4 VERHARDER WINTERCURE

(Contd. of page 10)

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Contact: J. Dijkstra

Date of previous version: 19.04.2023 · Version number of previous version: 34

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Sources

- ECHA European Chemical Agency http://echa.europa.eu/information-on-chemicals
- SDS of raw materials supplied by producer/supplier.
- * Data compared to the previous version altered.