



Printing date 06.02.2025 Version: 27 (replaces version 26) Revision: 06.02.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name: ZANCOR ZF-50

· Article number: C64-1

· UFI: 9U4S-90DM-G00T-6FY6

1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC7 Industrial spraying

PROC10 Roller application or brushing

PROC19 Manual activities involving hand contact PROC13 Treatment of articles by dipping and pouring

· Application of the substance / the mixture solvent based, one component alkyd coating

#### · 1.3 Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

Zandleven Coatings B.V.

Snekertrekweg 57-59, 8912 AA Leeuwarden, Netherlands

Tel: +31 58 2129545 Fax: +31 58 2155996

E-mail: info@zandleven.com Internet: www.zandleven.com

· Further information obtainable from: R&D department: sds@zandleven.com

## · 1.4 Emergency telephone number:

Nationaal Vergiftigingen Informatie

+31 (0)88 755 8000

ORFILA (INRS): + 33 (0)1 45 42 59 59 Centres Antipoison et de Toxicovigilance

ANGERS: 02 41 48 21 21 BORDEAUX: 05 56 96 40 80 LILLE: 0800 59 59 59 LYON: 04 72 11 69 11 MARSEILLE: 04 91 75 25 25 NANCY: 03 83 22 50 50 PARIS: 01 40 05 48 48 STRASBOURG: 03 88 37 37 37

STRASBOURG: 03 88 37 37 37 TOULOUSE: 05 61 77 74 47

Giftnotruf der Charité, Berlin: 030/19240

Giftinformationszentrum-Nord der Länder Bremen, Hamburg, Niedersachsen und Schleswig-Holstein (GIZ-

Nord):0551/19 240

Informationszentrale gegen Vergiftungen Zentrum für Kinderheilkunde Universitätsklinikum Bonn: 0228/19240 Giftnotruf Erfurt Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen,

Sachsen-Anhalt und Thüringen: 0361/730 730

Informations- und Beratungszentrum für Vergiftungsfälle Klinik für Kinder- und Jugendmedizin

Universitätsklinikum des Saarlandes: 06841/19240

Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen - Klinische Toxikologie - Universitätsmedizin der Johannes Gutenberg-Universität Mainz: 06131/19240

Vergiftungs-Informations-Zentrale Zentrum für Kinder- und Jugendmedizin Universitätsklinikum: 0761/19240 Giftnotruf München Toxikologische Abteilung der II. Med. Klinik und Poliklinik: 089/19240

+31 (0)58 2677590 (during office hours)

### **SECTION 2: Hazards identification**

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour. Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation. STOT SE 3 H335 May cause respiratory irritation.

(Contd. on page 2)



Printing date 06.02.2025 Version: 27 (replaces version 26) Revision: 06.02.2025

Trade name: ZANCOR ZF-50

(Contd. of page 1)

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





- · Signal word Warning
- · Hazard-determining components of labelling:

xylene

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H335 May cause respiratory irritation.

H412 Harmful to aquatic life with long lasting effects.

**Precautionary statements** 

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water

[or shower].

P305+P351+P338 İF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- Dangerous components:

Percentages of the components are expressed as a percentage by weight

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	25-50%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	2.5-10%
CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32	Zinc oxide	1-2.5%
CAS: 78-83-1 EINECS: 201-148-0 Index number: 603-108-00-1 Reg.nr.: 01-2119484609-23	butanol ∳ Flam. Liq. 3, H226; ∜ Eye Dam. 1, H318; ∜ Skin Irrit. 2, H315; STOT SE 3, H335-H336	1-2.5%

(Contd. on page 3)



Printing date 06.02.2025 Version: 27 (replaces version 26) Revision: 06.02.2025

Trade name: ZANCOR ZF-50

Additional information: For the wording of the listed hazard phrases refer to section 16.

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 4)



Printing date 06.02.2025 Version: 27 (replaces version 26) Revision: 06.02.2025

Trade name: ZANCOR ZF-50

(Contd. of page 3)

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store material in original, well-closed packages in a cool, well-ventilated area according to local regulations.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Recommended storage temperature: 5 30 °C
- · 7.3 Specific end use(s) No further relevant information available.

## SECTION 8: Exposure controls/personal protection

1330-20-7	ts with limit values that require mo		<u> </u>
	nort-term value: 442 mg/m³, 100 ppm		
Lo	ng-term value: 221 mg/m³, 50 ppm		
Sk	*** *		
	ethylbenzene		
	nort-term value: 884 mg/m³, 200 ppm		
Sk	ng-term value: 442 mg/m³, 100 ppm		
	rived No Effect Level) for workers:		
1330-20-7			
Dermal	Long-term - systemic effects, worker	212 ma/ka	bw/day (worker)
	Acute - systemic effects, worker	442 mg/m <sup>3</sup>	,
	Acute - local effects, worker	442 mg/m <sup>3</sup>	
	Long-term - systemic effects, worker	1	` ,
	Long-term - local effects, worker	221 mg/m <sup>3</sup>	
100-41-4	ethylbenzene	J - J	,
Dermal	Long-term - systemic effects, worker	180 mg/kg	bw/day (worker)
Inhalative	Acute - local effects, worker	293 mg/m <sup>3</sup>	(worker)
	Long-term - systemic effects, worker	77 mg/m³ (	worker)
1314-13-2	Zinc oxide		
Dermal	Long-term - systemic effects, worker	83 mg/kg b	w/day (worker)
Inhalative	Long-term - systemic effects, worker	5 mg/m³ (w	rorker)
78-83-1 bi	utanol	•	
Inhalative	Long-term - local effects, worker	310 mg/m <sup>3</sup>	(worker)
DNEL (De	rived No Effect Level) for the gener	al polulatio	n:
1330-20-7			
Oral	Long-term - systemic effects, genera	I population	12.5 mg/kg bw/day (general population)
Dermal			125 mg/kg bw/day (general population)
Inhalative	Acute - systemic effects, general pop		260 mg/m³ (general population)
	Acute - local effects, general populat		260 mg/m³ (general population)
	Long-term - systemic effects, genera		
	Long-term - local effects, general pop	oulation	65.3 mg/m³ (general population)
	ethylbenzene		
Oral			1.6 mg/kg bw/day (general population)
	Long-term - systemic effects, genera	l population	15 mg/m³ (general population)
	Zinc oxide		
Oral			0.83 mg/kg bw/day (general population)
Dermal	Long-term - systemic effects, genera	I population	83 mg/kg bw/day (general population)



Printing date 06.02.2025 Version: 27 (replaces version 26) Revision: 06.02.2025

Trade name: ZANCOR ZF-50

78-83-1 butanol	(Contd. of p	
Inhalative Long-term - local effects, general popula	tion 55 mg/m³ (general population)	
PNEC (Predicted No Effect Concentration) values:		
1330-20-7 xylene		
Aquatic compartment - freshwater	0.327 mg/L (freshwater)	
Aquatic compartment - marine water	0.327 mg/L (marine water)	
Aquatic compartment - water, intermittent releases	0.327 mg/L (intermittent release water)	
Aquatic compartment - sediment in freshwater	12.46 mg/kg sed dw (sediment fresh water)	
Aquatic compartment - sediment in marine water	12.46 mg/kg sed dw (sediment marine water)	
Terrestrial compartment - soil	2.31 mg/kg dw (soil)	
Sewage treatment plant	6.58 mg/L (sewage treatment plant)	
100-41-4 ethylbenzene		
Aquatic compartment - freshwater	0.1 mg/L (not specified)	
Aquatic compartment - marine water	0.01 mg/L (not specified)	
Aquatic compartment - water, intermittent releases	0.1 mg/L (not specified)	
Aquatic compartment - sediment in freshwater	13.7 mg/kg sed dw (not specified)	
Aquatic compartment - sediment in marine water	1.37 mg/kg sed dw (not specified)	
Terrestrial compartment - soil	2.68 mg/kg dw (not specified)	
Sewage treatment plant	9.6 mg/L (not specified)	
Oral secondary poisoning	0.02 mg/kg food (not specified)	
1314-13-2 Zinc oxide		
Aquatic compartment - freshwater	0.0206 mg/L (not specified)	
Aquatic compartment - marine water	0.0061 mg/L (not specified)	
Aquatic compartment - sediment in freshwater	117.8 mg/kg sed dw (not specified)	
Aquatic compartment - sediment in marine water	56.5 mg/kg sed dw (not specified)	
Terrestrial compartment - soil	35.6 mg/kg dw (not specified)	
Sewage treatment plant	0.1 mg/L (not specified)	
78-83-1 butanol		
Aquatic compartment - freshwater	0.4 mg/L (freshwater)	
Aquatic compartment - marine water	0.04 mg/L (marine water)	
	11 mg/L (intermittent release water)	
Aquatic compartment - sediment in freshwater	1.52 mg/kg sed dw (sediment fresh water)	
Aquatic compartment - sediment in marine water	0.152 mg/kg sed dw (sediment marine water)	
Terrestrial compartment - soil	0.0699 mg/kg dw (not specified)	
Sewage treatment plant	10 mg/L (sewage treatment plant)	
84418-68-8 Zinc neodecanoat		
Aquatic compartment - freshwater	0.0896 mg/L (freshwater)	
Aquatic compartment - marine water	0.0265 mg/L (marine water)	
Aquatic compartment - sediment in freshwater	512.2 mg/kg sed dw (sediment fresh water)	
Aquatic compartment - sediment in marine water	245.7 mg/kg sed dw (sediment marine water)	
Terrestrial compartment - soil	154.8 mg/kg dw (soil)	
Sewage treatment plant	0.4348 mg/L (sewage treatment plant)	

Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne

contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

Appropriate engineering controls No further data; see section 7.

(Contd. on page 6)





Printing date 06.02.2025 Version: 27 (replaces version 26) Revision: 06.02.2025

Trade name: ZANCOR ZF-50

(Contd. of page 5)

#### Individual protection measures, such as personal protective equipment

#### · General protective and hygienic measures:

Provide readily accessible eye wash stations and safety showers.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If

workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed

respirator complying with an approved standard if a risk assessment indicates this is necessary.

For organic vapors and solvents type of filter A1 or A2, for dust type of filter P (according to EN 140)

#### Hand protection



Protective gloves

Chemical resistant gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

#### Penetration time of glove material

KCL Vitoject 890

breakthrough time > 480 min.

thickness: 0,7 mm

at limited contact

KCL Camatril 730

breakthrough time 30 min.

thickness: 0,4 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed

- · Not suitable are gloves made of the following materials: All other materials
- · Eye/face protection



Tightly sealed goggles

Safety glasses according to EN 166 or equivalent

### · Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved before the product is used by a specialist.

If there is a risk of ignition by static electricity, anti-static protective clothing should be worn. For the best protection against static discharge, clothing should consist of anti-static overalls, boots and gloves. For further information on materials and design requirements and test methods consult the European standard EN 1149.

## Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

- EU

Page 7/11



## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.02.2025 Version: 27 (replaces version 26) Revision: 06.02.2025

Trade name: ZANCOR ZF-50

(Contd. of page 6)

## SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

· General Information

· Physical state Liquid

Colour: According to product specification

· Odour: Characteristic · Odour threshold: Not determined. • Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range 136 °C (100-41-4 ethylbenzene) · Flammability Flammable.

Lower and upper explosion limit

1.1 Vol % (1330-20-7 xylene) · Lower: · Upper: 7 Vol % (1330-20-7 xylene) · Flash point: 30 °C (1330-20-7 xylene) · Auto-ignition temperature: 430 °C (100-41-4 ethylbenzene)

Decomposition temperature: Not determined.

· pH Not determined.

· Viscosity:

Kinematic viscosity at 40 °C: > 20,5 mm<sup>2</sup>/s

· Dynamic at 20 °C: 800 mPas

· Solubility

· water: Not miscible or difficult to mix.

· Partition coefficient n-octanol/water (log value) Not determined.

· Vapour pressure at 20 °C: 6.7-8.2 hPa (1330-20-7 xylene)

Density and/or relative density

· Density at 20 °C: ~1.22-~1.23 g/cm3 · Relative density Not determined. Not determined. · Vapour density

· 9.2 Other information

· Appearance:

· Form: Fluid

· Important information on protection of health and

environment, and on safety.

Product is not selfigniting. · Ignition temperature:

Explosive properties: Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Change in condition

· Evaporation rate Not determined.

· Information with regard to physical hazard classes

· Explosives Void Flammable gases Void Void · Aerosols Oxidising gases Void · Gases under pressure Void

Flammable liquids Flammable liquid and vapour.

Flammable solids Void · Self-reactive substances and mixtures Void · Pyrophoric liquids Void · Pyrophoric solids Void Self-heating substances and mixtures Void Substances and mixtures, which emit flammable

gases in contact with water Void Oxidising liquids Void Void · Oxidising solids Organic peroxides Void · Corrosive to metals Void

(Contd. on page 8)



Printing date 06.02.2025 Version: 27 (replaces version 26) Revision: 06.02.2025

Trade name: ZANCOR ZF-50

(Contd. of page 7)

· Desensitised explosives

Void

## SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC5	LD/LC50 values relevant for classification: 1330-20-7 xylene		
1330-20			
Oral	LD50	3,523 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
100-41-	4 ethy	benzene	
Oral	LD50	3,500 mg/kg (rat)	
Dermal	LD50	17,800 mg/kg (rabbit)	
1314-13	-2 Zin	c oxide	
Oral	LD50	>5,000 mg/kg (rat)	
1	78-83-1 butanol		
Oral	LD50	2,460 mg/kg (rat)	
Dermal	LD50	3,400 mg/kg (rabbit)	
84418-6	84418-68-8 Zinc neodecanoat		
Oral	LD50	2,000-5,000 mg/kg (mouse)	
		3,640 mg/kg (rat)	

- · Primary irritant effect:
- · Skin corrosion/irritation Causes skin irritation.
- · Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure May cause respiratory irritation.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

## **SECTION 12: Ecological information**

· 12.1 Toxicity

· Aquatic toxicity:	
1330-20-7 xylene	
EC50/72 h 2.2 mg/l (algae)	
EC50/48 h >3.4 mg/l (Ceriodaphnia dubia)	

(Contd. on page 9)



Printing date 06.02.2025 Version: 27 (replaces version 26) Revision: 06.02.2025

Trade name: ZANCOR ZF-50

		(Contd. of page 8)
ſ	LC50/96 h	2.6 mg/l (Oncorhynchus mykiss)
İ	LC50/24 h	1 mg/l (Daphnia magna)
	100-41-4 et	hylbenzene
	EC50/72 h	3.6-4.2 mg/l (algae)
İ	EC50/24 h	2.2 mg/l (Daphnia magna)
İ	LC50/96 h	4.2 mg/l (Oncorhynchus mykiss)
Ī	1314-13-2	Zinc oxide
ſ	EC50/72 h	0.21 mg/l (algae)
		0.67 mg/l (Ceriodaphnia dubia)
Ī	78-83-1 but	tanol
Ī	LC50/96 h	1.33-2.03 mg/l (fish)
İ	LC50/48 h	1.03-1.19 mg/l (crustaceans)
Ī		Zinc neodecanoat
ſ	EC50/48 h	0.155-2.909 mg/l (aquatic invertebrates)
İ	LC50/96 h	0.112-2.92 mg/l (fish)
		4

- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

## SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European	waste catalogue
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
08 01 00	wastes from MFSU and removal of paint and varnish
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances
HP3	Flammable
HP4	Irritant - skin irritation and eye damage
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity
HP6	Acute Toxicity
HP14	Ecotoxic

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

Page 10/11



# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.02.2025 Version: 27 (replaces version 26) Revision: 06.02.2025

Trade name: ZANCOR ZF-50

(Contd. of page 9)

SECTION 14: Transport information	tion
Transport in accordance with ADR/RID, IM	IDG and ICAO/IATA.
· 14.1 UN number or ID number · ADR/RID/ADN, IMDG · IATA	Void UN1263
· 14.2 UN proper shipping name · ADR/RID/ADN, IMDG · IATA	Void PAINT
· 14.3 Transport hazard class(es)	
· ADR/RID/ADN, ADN, IMDG · Class · IATA	Void
Class	3 Flammable liquids.
Label	3
· 14.4 Packing group · ADR/RID/ADN, IMDG · IATA	Void III
· 14.5 Environmental hazards: · Marine pollutant:	Yes
· 14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk accordir instruments	ng to IMO Not applicable.
· Transport/Additional information:	
· ADR/RID/ADN	
· Remarks:	Up to 450 litre exempted according to ADR 2.2.3.1.5.
· IMDG · Remarks:	Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code.
· IATA · Remarks:	The "viscosity exemption" provisions do NOT apply to a transport.
· UN "Model Regulation":	Void

## **SECTION 15: Regulatory information**

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- $\cdot$  Qualifying quantity (tonnes) for the application of lower-tier requirements  $5{,}000\ t$
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment Annex II

None of the ingredients is listed.

(Contd. on page 11)

Page 11/11



## Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.02.2025 Version: 27 (replaces version 26) Revision: 06.02.2025

Trade name: ZANCOR ZF-50

REGULATION (EU) 2019/1148

(Contd. of page 10)

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS** 

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

108-88-3 toluene

3

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

108-88-3 toluene

3

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Department issuing SDS: Product safety department.

· Contact: J. Dijkstra

· Date of previous version: 19.04.2023 · Version number of previous version: 26

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Skin Irrit. 2: Skin corrosion/irritation - Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Sources

- ECHA European Chemical Agency - http://echa.europa.eu/information-on-chemicals

SDS of raw materials supplied by producer/supplier.

\* Data compared to the previous version altered.