Printing date 06.02.2025

Version: 18 (replaces version 17)

Revision: 06.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Trade name: <u>POLYFINISH GOLDSTAR</u> Article number: D44GOLDSTAR · UFI: W42C-Y1S8-J00Q-PH1G 1.2 Relevant identified uses of the substance or mixture and uses advised against Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU19 Building and construction work SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC9a Coatings and paints, thinners, paint removers Process category PROC7 Industrial spraying PROC10 Roller application or brushing PROC19 Manual activities involving hand contact PROC13 Treatment of articles by dipping and pouring · Application of the substance / the mixture solvent based, two component polyurethane coating base 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Zandleven Coatings B.V. Snekertrekweg 57-59, 8912 AA Leeuwarden, Netherlands Tel: +31 58 2129545 Fax: +31 58 2155996 E-mail: info@zandleven.com Internet: www.zandleven.com · Further information obtainable from: R&D department: sds@zandleven.com · 1.4 Emergency telephone number: Nationaal Vergiftigingen Informatie +31 (0)88 755 8000 ORFILA (INRS) : + 33 (0)1 45 42 59 59 Centres Antipoison et de Toxicovigilance ANGERS: 02 41 48 21 21 BORDEAUX: 05 56 96 40 80 LILLE: 0800 59 59 59 LYON: 04 72 11 69 11 MARSEILLE: 04 91 75 25 25 NANCY: 03 83 22 50 50 PARIS: 01 40 05 48 48 STRASBOURG: 03 88 37 37 37 TOULOUSE: 05 61 77 74 47 Giftnotruf der Charité, Berlin: 030/19240 Giftinformationszentrum-Nord der Länder Bremen, Hamburg, Niedersachsen und Schleswig-Holstein (GIZ-Nord) :0551/19 240 Informationszentrale gegen Vergiftungen Zentrum für Kinderheilkunde Universitätsklinikum Bonn: 0228/19240 Giftnotruf Erfurt Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen: 0361/730 730 Informations- und Beratungszentrum für Vergiftungsfälle Klinik für Kinder- und Jugendmedizin Universitätsklinikum des Saarlandes: 06841/19240 Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen - Klinische Toxikologie - Universitätsmedizin der Johannes Gutenberg-Universität Mainz: 06131/19240 Vergiftungs-Informations-Zentrale Zentrum für Kinder- und Jugendmedizin Universitätsklinikum: 0761/19240 Giftnotruf München Toxikologische Abteilung der II. Med. Klinik und Poliklinik: 089/19240 Supplier +31 (0)58 2677590 (during office hours) **SECTION 2: Hazards identification** 

# • 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Lig. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)

EU


Printing date 06.02.2025

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version: 18 (replaces version 17)

Revision: 06.02.2025

Trade name: POLYFINISH GOLDSTAR



• **vPvB:** Not applicable.

# SECTION 3: Composition/information on ingredients

 $\cdot$  **Description:** Mixture of substances listed below with nonhazardous additions.

# · Dangerous components:

Percentages of the components are expressed as a percentage by weight

CAS: 123-86-4 EINECS: 204-658-1	n-butyl acetate Flam. Lig. 3, H226;  \$STOT SE 3, H336, EUH066	10-25%
Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29		
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	10-25%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226;  STOT SE 3, H336	2.5-10%
CAS: 128601-23-0 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	C9-aromatics Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Aquatic Chronic 2, H411;  Acute Tox. 4, H312; STOT SE 3, H335-H336, EUH066	2.5-10%
Reg.nr.: 01-2119455851-35	H411; 🚯 Acute Tox. 4, H312; STOT SE 3, H335-H336, EUH066	td. on pa

<sup>· 3.2</sup> Mixtures

Printing date 06.02.2025

Version: 18 (replaces version 17)

Revision: 06.02.2025

#### Trade name: POLYFINISH GOLDSTAR

	ethylbenzene Flam. Liq. 2, H225;    STOT RE 2, H373; Asp. Tox. 1, H304;	ntd. of page 2) 0-10%
EINECS: 212-782-2 Index number: 607-124-00-X Reg.nr.: 01-2119490169-29	2-hydroxyethyl methacrylate Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	<1%
• Additional information: For	the wording of the listed hazard phrases refer to section 16.	

#### SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- Information about fire and explosion protection:
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.

(Contd. on page 4)

<sup>–</sup> EU

Printing date 06.02.2025

Version: 18 (replaces version 17)

Revision: 06.02.2025

### Trade name: POLYFINISH GOLDSTAR

(Contd. of page 3)

- $^{\cdot}$  7.2 Conditions for safe storage, including any incompatibilities
- · Storage:

· Requirements to be met by storerooms and receptacles:

Store material in original, well-closed packages in a cool, well-ventilated area according to local regulations.

Information about storage in one common storage facility: Not required.
 Further information about storage conditions: Keep container tightly sealed.

• Recommended storage temperature: 5 - 30 °C

7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

-	nts with limit values that require mo	miloring at the workplace:	
	n-butyl acetate		
IOELV	Short-term value: 723 mg/m³, 150 ppm .ong-term value: 241 mg/m³, 50 ppm		
	<b>. .7 xylene</b>		
	Short-term value: 442 mg/m <sup>3</sup> , 100 ppm		
	ong-term value: 221 mg/m³, 50 ppm		
	Skin		
108-65-6	2-methoxy-1-methylethyl acetate		
	Short-term value: 550 mg/m <sup>3</sup> , 100 ppm		
	ong-term value: 275 mg/m³, 50 ppm		
	Skin		
	ethylbenzene		
	Short-term value: 884 mg/m <sup>3</sup> , 200 ppm		
	ong-term value: 442 mg/m³, 100 ppm Skin		
	Perived No Effect Level) for workers:		
•			
Dermal	Acute - systemic effects, worker	11 mg/kg bw/day (human)	
Dermai	-		
ب المعامة ا	Long-term - systemic effects, worker		
Innalativ	e Acute - systemic effects, worker	600 mg/m <sup>3</sup> (human)	
	Acute - local effects, worker	600 mg/m³ (human)	
	Long-term - systemic effects, worker		
1000.00	Long-term - local effects, worker	300 mg/m³ (human)	
	-7 xylene		
Dermal	Long-term - systemic effects, worker		
Inhalativ	e Acute - systemic effects, worker	442 mg/m <sup>3</sup> (worker)	
	Acute - local effects, worker	442 mg/m <sup>3</sup> (worker)	
	Long-term - systemic effects, worker		
	Long-term - local effects, worker	221 mg/m³ (worker)	
	2-methoxy-1-methylethyl acetate	1	
Dermal	Long-term - systemic effects, worker	,	
	e Long-term - systemic effects, worker	275 mg/m³ (worker)	
	23-0 C9-aromatics		
Dermal	Long-term - systemic effects, worker		
	e Long-term - systemic effects, worker	151 mg/m³ (human)	
	ethylbenzene		
Dermal	Long-term - systemic effects, worker		
Inhalativ	e Acute - local effects, worker	293 mg/m³ (worker)	
	Long-term - systemic effects, worker	77 mg/m <sup>3</sup> (worker)	

EU

Printing date 06.02.2025

Version: 18 (replaces version 17)

Revision: 06.02.2025

Trade name: POLYFINISH GOLDSTAR

	rived No Effect Lovel) for the remarks		(Contd.	of pa
-	rived No Effect Level) for the general p n-butyl acetate	olulatio	1:	
Oral	Acute - systemic effects, general popula	tion	2 mg/kg bw/day (human)	
Orai	Long-term - systemic effects, general popula			
Dermal	Acute - systemic effects, general polulat	-	6 mg/kg bw/day (human)	
Dennai				
Inholotivo	Long-term - systemic effects, general po			
Innalative	Acute - systemic effects, general popula		300 mg/m <sup>3</sup> (general population)	
	Acute - local effects, general population		300 mg/m³ (human)	
	Long-term - systemic effects, general po	-		
4000 00 7	Long-term - local effects, general popula	ation	35.7 mg/m³ (human)	
1330-20-7	xylene Long-term - systemic effects, general po	nulation	12.5 mg/kg bw/dov (gonoral population)	
Oral Dermal	Long-term - systemic effects, general po			
		-		
Innalative	Acute - systemic effects, general popula		260 mg/m <sup>3</sup> (general population)	
	Acute - local effects, general population		260 mg/m <sup>3</sup> (general population)	
	Long-term - systemic effects, general po			
100.07.0	Long-term - local effects, general popula	ation	65.3 mg/m³ (general population)	
	2-methoxy-1-methylethyl acetate		4.07 mm//m hu/day/manageneral namulation)	
Oral	Long-term - systemic effects, general po		,	
Dermal	Long-term - systemic effects, general po			
	Long-term - systemic effects, general po	pulation	33 mg/m <sup>°</sup> (general population)	
	3-0 C9-aromatics	nulation	7.5 mg/kg hu/dou (humon)	
Oral	Long-term - systemic effects, general po			
Dermal	Long-term - systemic effects, general po			
	Long-term - systemic effects, general po	pulation	32 mg/m² (numan)	
Oral	e <b>thylbenzene</b> Long-term - systemic effects, general po	nulation	1.6 mailes buildou (sonorol population)	
	Long-term - systemic effects, general po	-		
		-		
•	edicted No Effect Concentration) value	es:		
	n-butyl acetate	0.10	(1 (free e burgter))	
-	mpartment - freshwater	-	/L (freshwater)	
-	mpartment - marine water		g/L (marine water)	
-	mpartment - water, intermittent releases	-		
-	mpartment - sediment in freshwater		g/kg sed dw (not specified)	
-	mpartment - sediment in marine water		ng/kg sed dw (not specified)	
	compartment - soil		ng/kg dw (not specified)	
-	eatment plant	35.6 mg	/L (not specified)	
1330-20-7	-	0.007	a ( fra a burata a)	
-	mpartment - freshwater		g/L (freshwater)	
-	mpartment - marine water		g/L (marine water)	
-	mpartment - water, intermittent releases		g/L (intermittent release water)	
•	mpartment - sediment in freshwater		g/kg sed dw (sediment fresh water)	
-	mpartment - sediment in marine water		g/kg sed dw (sediment marine water)	
	compartment - soil	-	/kg dw (soil)	
-	eatment plant	6.58 mg	/L (sewage treatment plant)	
	2-methoxy-1-methylethyl acetate	0.005		
-	mpartment - freshwater		g/L (not specified)	
-	mpartment - marine water		ng/L (not specified)	
Aduatic co	mpartment - water, intermittent releases	6.35 mg	/L (not specified)	
-	mpartment - sediment in freshwater		/kg sed dw (not specified)	

Printing date 06.02.2025

Version: 18 (replaces version 17)

Revision: 06.02.2025

#### Trade name: POLYFINISH GOLDSTAR

	(Contd. of page 5	5)
Aquatic compartment - sediment in marine water	0.329 mg/kg sed dw (not specified)	7
Terrestrial compartment - soil	0.29 mg/kg dw (not specified)	
Sewage treatment plant	100 mg/L (not specified)	
100-41-4 ethylbenzene		1
Aquatic compartment - freshwater	0.1 mg/L (not specified)	-
Aquatic compartment - marine water	0.01 mg/L (not specified)	
Aquatic compartment - water, intermittent releases	0.1 mg/L (not specified)	
Aquatic compartment - sediment in freshwater	13.7 mg/kg sed dw (not specified)	
Aquatic compartment - sediment in marine water	1.37 mg/kg sed dw (not specified)	
Terrestrial compartment - soil	2.68 mg/kg dw (not specified)	
Sewage treatment plant	9.6 mg/L (not specified)	
Oral secondary poisoning	0.02 mg/kg food (not specified)	

· Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne

contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. **Appropriate engineering controls** No further data; see section 7.

### Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures:

Provide readily accessible eye wash stations and safety showers.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin. Avoid contact with the eyes and skin.

Respiratory protection:

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If

workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed

respirator complying with an approved standard if a risk assessment indicates this is necessary.

For organic vapors and solvents type of filter A1 or A2, for dust type of filter P (according to EN 140) Hand protection



Protective gloves

Chemical resistant gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Butyl rubber, BR

Penetration time of glove material

KCL Butoject 898

breakthrough time 60 min.

thickness: 0,7 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Not suitable are gloves made of the following materials: All other materials

(Contd. on page 7)

FU

280

Printing date 06.02.2025

Version: 18 (replaces version 17)

Revision: 06.02.2025

#### Trade name: POLYFINISH GOLDSTAR

(Contd. of page 6)

Tightly sealed goggles

Safety glasses according to EN 166 or equivalent

#### Body protection:

· Eye/face protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved before the product is used by a specialist.

If there is a risk of ignition by static electricity, anti-static protective clothing should be worn. For the best protection against static discharge, clothing should consist of anti-static overalls, boots and gloves. For further information on materials and design requirements and test methods consult the European standard EN 1149.

#### Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical pro	operties
· General Information	
<sup>·</sup> Physical state	Liquid
· Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
<ul> <li>Melting point/freezing point:</li> </ul>	Undetermined.
Boiling point or initial boiling point and boiling	
range	124-128 °C (123-86-4 n-butyl acetate)
Flammability	Flammable.
· Lower and upper explosion limit	
· Lower:	1.1 Vol % (1330-20-7 xylene)
· Upper:	7.5 Vol % (123-86-4 n-butyl acetate)
· Flash point:	30 °C
• Auto-ignition temperature:	315 °C (108-65-6 2-methoxy-1-methylethyl acetate)
Decomposition temperature:	Not determined.
· pH	Not determined.
Viscosity:	
· Kinematic viscosity	at 40 °C: > 20,5 mm²/s
· Dynamic at 20 °C:	600 mPas
Solubility	
· water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure at 20 °C:	10.7 hPa (123-86-4 n-butyl acetate)
· Vapour pressure at 50 °C:	55 hPa
· Density and/or relative density	
· Density at 20 °C:	1.01 g/cm³
· Relative density	Not determined.
· Vapour density	Not determined.
9.2 Other information	
· Appearance: · Form:	Fluid
	Fluid
Important information on protection of health and     anyironment, and an apfety.	
environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product is not explosive. However, formation of
	explosive air/vapour mixtures are possible.

EU

### Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.02.2025

Version: 18 (replaces version 17)

Revision: 06.02.2025

#### Trade name: POLYFINISH GOLDSTAR

		(Contd. of page 7)
· Change in condition		
· Evaporation rate	Not determined.	
· Information with regard to physical hazard c	lasses	
Explosives	Void	
· Flammable gases	Void	
Aerosols	Void	
· Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Flammable liquid and vapour.	
· Flammable solids	Void	
<ul> <li>Self-reactive substances and mixtures</li> </ul>	Void	
· Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
· Oxidising liquids	Void	
Oxidising solids	Void	
· Organic peroxides	Void	
Corrosive to metals	Void	
· Desensitised explosives	Void	

#### SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

• 10.4 Conditions to avoid No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 v	alues rele	evant for classification:
123-86-4 r	n-butyl ace	etate
Oral	LD50	10,760 mg/kg (rat)
Dermal	LD50	>17,600 mg/kg (rabbit)
Inhalative	LC50/4 h	23.4 mg/l (rat)
1330-20-7	xylene	
Oral	LD50	3,523 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
108-65-6 2	2-methoxy	r-1-methylethyl acetate
Oral	LD50	8,532 mg/kg (rat)
Inhalative	LC50/4 h	35.7 mg/l (rat)
128601-23	-0 C9-aro	matics
Oral	LD50	5,558-7,093 mg/kg (rat)
Dermal	LD50	2,000-3,160 mg/kg (rabbit)
100-41-4 e	thylbenze	ene
Oral	LD50	3,500 mg/kg (rat)
Dermal	LD50	17,800 mg/kg (rabbit)
		(Contd. on page

Printing date 06.02.2025

Version: 18 (replaces version 17)

Revision: 06.02.2025

(Contd. of page 8)

#### Trade name: POLYFINISH GOLDSTAR

#### 868-77-9 2-hydroxyethyl methacrylate

## Oral LD50 5,050 mg/kg (rat)

Primary irritant effect:

· Skin corrosion/irritation Causes skin irritation.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

· Carcinogenicity Based on available data, the classification criteria are not met.

· Reproductive toxicity Based on available data, the classification criteria are not met.

· STOT-single exposure Based on available data, the classification criteria are not met.

· STOT-repeated exposure Based on available data, the classification criteria are not met.

· Aspiration hazard Based on available data, the classification criteria are not met.

· 11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

### SECTION 12: Ecological information

#### · 12.1 Toxicity

Aquatic toxic	ity:			
123-86-4 n-bu	tyl acetate			
EC50/72 h	647.7 mg/l (algae)			
EC50/48 h	44 mg/l (Daphnia magna)			
EC50/24 h	335 mg/l (aquatic algae and cyanobacteria)			
LC50/96 h	18 mg/l (pimephales promelas)			
NOEC 21 days	s 23.2 mg/l (aquatic invertebrates)			
1330-20-7 xyl	ene			
EC50/72 h	2.2 mg/l (algae)			
EC50/48 h	>3.4 mg/l (Ceriodaphnia dubia)			
LC50/96 h	2.6 mg/l (Oncorhynchus mykiss)			
LC50/24 h	LC50/24 h 1 mg/l (Daphnia magna)			
108-65-6 2-me	ethoxy-1-methylethyl acetate			
EC50/48 h	408-500 mg/l (Daphnia magna)			
LC50/96 h	LC50/96 h 100-180 mg/l (Oncorhynchus mykiss)			
100-41-4 ethy	Ibenzene			
EC50/72 h	3.6-4.2 mg/l (algae)			
EC50/24 h	2.2 mg/l (Daphnia magna)			
LC50/96 h	LC50/96 h 4.2 mg/l (Oncorhynchus mykiss)			
• 12.3 Bioaccur • 12.4 Mobility • 12.5 Results o • PBT: Not appl • vPvB: Not app				
12.7 Other ad				

12.7 Other adverse effects

· Remark: Harmful to fish

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

(Contd. on page 10)

EU

Printing date 06.02.2025

Version: 18 (replaces version 17)

Revision: 06.02.2025

#### Trade name: POLYFINISH GOLDSTAR

Harmful to aquatic organisms

(Contd. of page 9)

# SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

Laiopean		
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS	
08 01 00	wastes from MFSU and removal of paint and varnish	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
HP3	Flammable	
HP14	Ecotoxic	

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

SECTION 14: Transport informati	
Transport in accordance with ADR/RID, IME	DG and ICAO/IATA.
14.1 UN number or ID number ADR/RID/ADN, ADN, IMDG IATA	Void UN1263
14.2 UN proper shipping name ADR/RID/ADN, ADN, IMDG IATA	Void PAINT
14.3 Transport hazard class(es)	
ADR/RID/ADN, ADN, IMDG Class	Void
Class	3 Flammable liquids.
Label	3
14.4 Packing group ADR/RID/ADN, IMDG IATA	Void III
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according instruments	g to IMO Not applicable.
Transport/Additional information:	
ADR/RID/ADN	
Remarks:	Up to 450 litre exempted according to ADR 2.2.3.1.5.
	(Contd. on page

Printing date 06.02.2025

Version: 18 (replaces version 17)

Revision: 06.02.2025

#### Trade name: POLYFINISH GOLDSTAR

	(Contd. of page 10
· IMDG · Remarks:	Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code.
· IATA · Remarks:	The "viscosity exemption" provisions do NOT apply to air transport.
· UN "Model Regulation":	Void

#### SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

- · Contact: J. Dijkstra
- · Date of previous version: 19.04.2023
- · Version number of previous version: 17
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

(Contd. on page 12)

Printing date 06.02.2025

Version: 18 (replaces version 17)

Revision: 06.02.2025

#### Trade name: POLYFINISH GOLDSTAR

(Contd. of page 11) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 · Sources - ECHA European Chemical Agency - http://echa.europa.eu/information-on-chemicals - SDS of raw materials supplied by producer/supplier.

\* Data compared to the previous version altered.