Printing date 06.02.2025

Version: 32 (replaces version 31)

Revision: 06.02.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Trade name: ACRYLEX AE-80 · Article number: D53-1 · UFI: 9C73-M1TM-D006-0331 · 1.2 Relevant identified uses of the substance or mixture and uses advised against Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU19 Building and construction work SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC9a Coatings and paints, thinners, paint removers Process category PROC7 Industrial spraying PROC10 Roller application or brushing PROC19 Manual activities involving hand contact PROC13 Treatment of articles by dipping and pouring · Application of the substance / the mixture waterborne, one component acrylic coating 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Zandleven Coatings B.V. Snekertrekweg 57-59, 8912 AA Leeuwarden, Netherlands Tel: +31 58 2129545 Fax: +31 58 2155996 E-mail: info@zandleven.com Internet: www.zandleven.com · Further information obtainable from: R&D department: sds@zandleven.com · 1.4 Emergency telephone number: Nationaal Vergiftigingen Informatie +31 (0)88 755 8000 ORFILA (INRS) : + 33 (0)1 45 42 59 59 Centres Antipoison et de Toxicovigilance ANGERS: 02 41 48 21 21 BORDEAUX: 05 56 96 40 80 LILLE: 0800 59 59 59 LYON: 04 72 11 69 11 MARSEILLE: 04 91 75 25 25 NANCY: 03 83 22 50 50 PARIS: 01 40 05 48 48 STRASBOURG: 03 88 37 37 37 TOULOUSE: 05 61 77 74 47 Giftnotruf der Charité, Berlin: 030/19240 Giftinformationszentrum-Nord der Länder Bremen, Hamburg, Niedersachsen und Schleswig-Holstein (GIZ-Nord) :0551/19 240 Informationszentrale gegen Vergiftungen Zentrum für Kinderheilkunde Universitätsklinikum Bonn: 0228/19240 Giftnotruf Erfurt Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen: 0361/730 730 Informations- und Beratungszentrum für Vergiftungsfälle Klinik für Kinder- und Jugendmedizin Universitätsklinikum des Saarlandes: 06841/19240 Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen - Klinische Toxikologie - Universitätsmedizin der Johannes Gutenberg-Universität Mainz: 06131/19240 Vergiftungs-Informations-Zentrale Zentrum für Kinder- und Jugendmedizin Universitätsklinikum: 0761/19240 Giftnotruf München Toxikologische Abteilung der II. Med. Klinik und Poliklinik: 089/19240 Supplier +31 (0)58 2677590 (during office hours) **SECTION 2: Hazards identification** · 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008
 The product is not classified, according to the CLP regulation.

## · 2.2 Label elements

· Labelling according to Regulation (EC) No 1272/2008 Void

· Hazard pictograms Void

(Contd. on page 2)

EU

Printing date 06.02.2025

Version: 32 (replaces version 31)

Revision: 06.02.2025

(Contd. of page 1)

## Trade name: ACRYLEX AE-80

· Signal word Void

## · Hazard statements Void

Additional information:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210 Safety data sheet available on request.

· 2.3 Other hazards

### Results of PBT and vPvB assessment

• **PBT:** Not applicable.

vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

#### · 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

#### · Dangerous components:

Percentages of the components are expressed as a percentage by weight

CAS: 112-34-5 EINECS: 249-951-5 Index number: 605-001-00-1 Reg.nr.: 01-2119475104-44	2-(2-butoxyethoxy)ethanol	1-2.5%
CAS: 2634-33-5 EINECS: 220-120-9 Index number: 613-088-00-6	1,2-benzisothiazol-3(2H)-one	0-<1%
CAS: 55965-84-9 Reg.nr.: 01-2120764691-48	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247- 500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1) Acute Tox. 3, H301; Acute Tox. 2, H310; Acute Tox. 2, H330; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=100); Aquatic Chronic 1, H410 (M=100); Skin Sens. 1A, H317, EUH071 Specific concentration limits: Skin Corr. 1C; H314: C ≥ 0.6 % Skin Irrit. 2; H315: 0.06 % ≤ C < 0.6 % Eye Dam. 1; H318: C ≥ 0.6 % Eye Irrit. 2; H319: 0.06 % ≤ C < 0.6 % Skin Sens. 1A; H317: C ≥ 0.0015 %	0-<1%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

## SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.

(Contd. on page 3)

Printing date 06.02.2025

Version: 32 (replaces version 31)

Revision: 06.02.2025

(Contd. of page 2)

#### Trade name: ACRYLEX AE-80

- 5.3 Advice for firefighters

• Protective equipment: No special measures required.

## SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- $^{\circ}$  6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
- 6.4 Reference to other sections
- No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

• 7.1 Precautions for safe handling Use only in well ventilated areas.

Information about fire - and explosion protection: No special measures required.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Store material in original, well-closed packages in a cool, well-ventilated area according to local regulations.

· Information about storage in one common storage facility: Not required.

• Further information about storage conditions: None.

· Recommended storage temperature: 5 - 30 °C

7.3 Specific end use(s) No further relevant information available.

# SECTION 8: Exposure controls/personal protection

#### · 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:						
112-34-5 2	112-34-5 2-(2-butoxyethoxy)ethanol					
	IOELV Short-term value: 101.2 mg/m³, 15 ppm					
Lo	Long-term value: 67.5 mg/m³, 10 ppm					
· DNEL (De	DNEL (Derived No Effect Level) for workers:					
112-34-5 2	112-34-5 2-(2-butoxyethoxy)ethanol					
Inhalative	Inhalative Acute - local effects, worker 101.2 mg/m³ (worker)					
Long-term - local effects, worker 67.5 mg/m <sup>3</sup> (worker)						
55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl- 2H-isothiazol-3-one [EC no. 220-239-6] (3:1)						
Inhalative	Acute - local effects, worker	0.04 mg/m <sup>3</sup> (wo	orker)			
	Long-term - local effects, worker 0.02 mg/m³ (worker)					
· DNEL (De	DNEL (Derived No Effect Level) for the general polulation:					
112-34-5 2	112-34-5 2-(2-butoxyethoxy)ethanol					
Oral	Oral Long-term - systemic effects, general population 6.25 mg/kg bw/day (general population)		6.25 mg/kg bw/day (general population)			
55965-84-9 reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl- 2H-isothiazol-3-one [EC no. 220-239-6] (3:1)						
Oral	Acute - systemic effects, general	population	0.11 mg/kg bw/day (general population)			
Long-term - systemic effects, general population Inhalative Acute - local effects, general population		0.09 mg/kg bw/day (general population)				
		ulation	0.04 mg/m³ (general population)			
	Long-term - local effects, general	population	0.02 mg/m³ (general population)			
			(Contd. on page 4)			

Printing date 06.02.2025

Version: 32 (replaces version 31)

Revision: 06.02.2025

Trade name: ACRYLEX AE-80

	(Contd. of page	
PNEC (Predicted No Effect Concentration) value	S:	
112-34-5 2-(2-butoxyethoxy)ethanol Aquatic compartment - freshwater	1.1 mg/L (freehundter)	
	1.1 mg/L (freshwater)	
Aquatic compartment - marine water	0.11 mg/L (marine water)	
	11 mg/L (intermittent release water)	
Aquatic compartment - sediment in freshwater	4.4 mg/kg sed dw (sediment fresh water)	
Aquatic compartment - sediment in marine water	0.44 mg/kg sed dw (sediment marine water)	
Terrestrial compartment - soil	0.32 mg/kg dw (soil)	
Oral secondary poisoning 55965-84-9 reaction mass of: 5-chloro-2-methyl-	56 mg/kg food (food sec poisoning) 4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-	
2H-isothiazol-3-one [EC no. 220-239-		
Aquatic compartment - freshwater	0.00339 mg/L (freshwater)	
Aquatic compartment - marine water	0.00339 mg/L (marine water)	
	0.00339 mg/L (intermittent release water)	
Aquatic compartment - sediment in freshwater	0.027 mg/kg sed dw (sediment fresh water)	
Aquatic compartment - sediment in marine water	0.027 mg/kg sed dw (sediment marine water)	
Terrestrial compartment - soil	0.01 mg/kg dw (soil)	
Sewage treatment plant	0.23 mg/L (sewage treatment plant)	
Additional information: The lists valid during the r	naking were used as basis.	
Wash hands before breaks and at the end of work. • Respiratory protection: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. For organic vapors and solvents type of filter A1 or A2, for dust type of filter P (according to EN 140) • Hand protection		
<ul> <li>Hand protection</li> <li>Chemical resistant gloves (EN 374)</li> <li>Check protective gloves prior to each use for their proper condition.</li> <li>The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.</li> <li>Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation</li> <li>Material of gloves</li> <li>The selection of the suitable gloves does not only depend on the material, but also on further marks of quality</li> </ul>		
and varies from manufacturer to manufacturer. As t resistance of the glove material can not be calculate application. Fluorocarbon rubber (Viton) Nitrile rubber, NBR <b>Penetration time of glove material</b> KCL Camatril 730 / KCL Dermatril 740 breakthrough time > 480 min. thickness: 0,4 / 0,11 mm	he product is a preparation of several substances, the ed in advance and has therefore to be checked prior to the the manufacturer of the protective gloves and has to be	
Body protection: Personal protective equipment for the body should		

Printing date 06.02.2025

Version: 32 (replaces version 31)

Revision: 06.02.2025

#### Trade name: ACRYLEX AE-80

(Contd. of page 4) If there is a risk of ignition by static electricity, anti-static protective clothing should be worn. For the best protection against static discharge, clothing should consist of anti-static overalls, boots and gloves. For further information on materials and design requirements and test methods consult the European standard EN 1149.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### SECTION 9: Physical and chemical properties 9.1 Information on basic physical and chemical properties · General Information Physical state Liquid · Colour: According to product specification · Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined. · Boiling point or initial boiling point and boiling 100 °C (7732-18-5 water, distilled, conductivity or of range similar purity) · Flammability Not applicable. Lower and upper explosion limit · Lower: Not determined. · Upper: Not determined. · Flash point: Not applicable. Decomposition temperature: Not determined. PH at 20 °C 7-9 · Viscosity: Kinematic viscosity at 40 °C: > 20,5 mm²/s · Dynamic at 20 °C: 600 mPas · Solubility · water: Fully miscible. · Partition coefficient n-octanol/water (log value) Not determined. · Vapour pressure at 20 °C: 23 hPa (7732-18-5 water, distilled, conductivity or of similar purity) · Density and/or relative density Density at 20 °C: >1.23-<1.26 g/cm3 Not determined. · Relative density · Vapour density Not determined. 9.2 Other information · Appearance: · Form: Fluid · Important information on protection of health and environment, and on safety. · Ignition temperature: Product is not selfigniting. · Explosive properties: Product does not present an explosion hazard. · Solvent content: · Water: 46.3 % · Change in condition · Evaporation rate Not determined. · Information with regard to physical hazard classes Explosives Void · Flammable gases Void · Aerosols Void Oxidising gases Void Gases under pressure Void · Flammable liquids Void (Contd. on page 6) EU

Printing date 06.02.2025

Version: 32 (replaces version 31)

Revision: 06.02.2025

Trade name: ACRYLEX AE-80

		(Contd. of page 5
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

# SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.

• **10.4 Conditions to avoid** No further relevant information available.

- $\cdot$  10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

• Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

112-34-5 2-(2-butoxyethoxy)ethanol

Oral LD50 5,660 mg/kg (rat)

Dermal LD50 2,764 mg/kg (rabbit)

Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

# SECTION 12: Ecological information

#### 12.1 Toxicity

- · Aquatic toxicity:
- 112-34-5 2-(2-butoxyethoxy)ethanol
- EC50/96 h 100 mg/l (aquatic algae and cyanobacteria)
- EC50/72 h 1,101 mg/l (aquatic algae and cyanobacteria)
- EC50/48 h 100 mg/l (aquatic invertebrates)

(Contd. on page 7)

EU

Printing date 06.02.2025

Version: 32 (replaces version 31)

Revision: 06.02.2025

(Contd. of page 6)

Trade name: ACRYLEX AE-80

#### LC50/96 h 1.3-2 mg/l (fish)

- 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

# SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

	•	
		WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS
	08 01 00	wastes from MFSU and removal of paint and varnish
_	00 04 44*	

08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

· Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

## SECTION 14: Transport information

The product is not classified as dangerous for transport according ADR/RID, IMDG and/or ICAO/IATA.

<ul> <li>14.1 UN number or ID number</li> <li>ADR/RID/ADN, ADN, IMDG, IATA</li> </ul>	Void	
<ul> <li>14.2 UN proper shipping name</li> <li>ADR/RID/ADN, ADN, IMDG, IATA</li> </ul>	Void	
· 14.3 Transport hazard class(es)		
· ADR/RID/ADN, ADN, IMDG, IATA · Class	Void	
<ul> <li>14.4 Packing group</li> <li>ADR/RID/ADN, IMDG, IATA</li> </ul>	Void	
<ul> <li>• 14.5 Environmental hazards:</li> <li>• Marine pollutant:</li> </ul>	No	
· 14.6 Special precautions for user	Not applicable.	
• 14.7 Maritime transport in bulk according to IMO instruments Not applicable.		
· UN "Model Regulation":	Void	
		EU

(Contd. on page 8)

Printing date 06.02.2025

Version: 32 (replaces version 31)

Revision: 06.02.2025

Trade name: ACRYLEX AE-80

(Contd. of page 7)

## **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Directive 2012/18/EU

• Named dangerous substances - ANNEX I None of the ingredients is listed.

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

**REGULATION (EU) 2019/1148** 

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

#### Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

## · Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Contact: J. Dijkstra

Date of previous version: 19.04.2023

· Version number of previous version: 31

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: verv Persistent and verv Bioaccumulative Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity - Category 4

Acute Tox. 2: Acute toxicity – Category 2 Skin Corr. 1C: Skin corrosion/irritation – Category 1C Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation - Category 1A

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Sources

- ECHA European Chemical Agency - http://echa.europa.eu/information-on-chemicals

SDS of raw materials supplied by producer/supplier.

\* Data compared to the previous version altered.