

Printing date 06.02.2025 Version: 15 (replaces version 14) Revision: 06.02.2025

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

Trade name: ACRATON WV-HB COATING

· Article number: D69-1 · UFI: N4YC-Y1SP-E001-AT0H

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU19 Building and construction work

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category PC9a Coatings and paints, thinners, paint removers

Process category

PROC7 Industrial spraying

PROC10 Roller application or brushing

PROC19 Manual activities involving hand contact PROC13 Treatment of articles by dipping and pouring

· Application of the substance / the mixture waterborne, two component epoxy coating base

· 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Zandleven Coatings B.V.

Snekertrekweg 57-59, 8912 AA Leeuwarden, Netherlands

Tel: +31 58 2129545 Fax: +31 58 2155996

E-mail: info@zandleven.com Internet: www.zandleven.com

· Further information obtainable from: R&D department: sds@zandleven.com

· 1.4 Emergency telephone number:

Nationaal Vergiftigingen Informatie

+31 (0)88 755 8000

ORFILA (INRS): + 33 (0)1 45 42 59 59 Centres Antipoison et de Toxicovigilance

ANGERS: 02 41 48 21 21 BORDEAUX: 05 56 96 40 80 LILLE: 0800 59 59 59 LYON: 04 72 11 69 11 MARSEILLE: 04 91 75 25 25 NANCY: 03 83 22 50 50 PARIS: 01 40 05 48 48 STRASBOURG: 03 88 37 37 37

STRASBOURG: 03 88 37 37 37 TOULOUSE: 05 61 77 74 47

Giftnotruf der Charité, Berlin: 030/19240

Giftinformationszentrum-Nord der Länder Bremen, Hamburg, Niedersachsen und Schleswig-Holstein (GIZ-

Nord):0551/19 240

Informationszentrale gegen Vergiftungen Zentrum für Kinderheilkunde Universitätsklinikum Bonn: 0228/19240 Giftnotruf Erfurt Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen,

Sachsen-Anhalt und Thüringen: 0361/730 730

Informations- und Beratungszentrum für Vergiftungsfälle Klinik für Kinder- und Jugendmedizin

Universitätsklinikum des Saarlandes: 06841/19240

Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen - Klinische Toxikologie - Universitätsmedizin der Johannes Gutenberg-Universität Mainz: 06131/19240

Vergiftungs-Informations-Zentrale Zentrum für Kinder- und Jugendmedizin Universitätsklinikum: 0761/19240 Giftnotruf München Toxikologische Abteilung der II. Med. Klinik und Poliklinik: 089/19240

+31 (0)58 2677590 (during office hours)

# SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

Skin Sens. 1 H317 May cause an allergic skin reaction.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

(Contd. on page 2)

(Contd. of page 1)



# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.02.2025 Version: 15 (replaces version 14) Revision: 06.02.2025

Trade name: ACRATON WV-HB COATING

· Hazard pictograms



- Signal word Warning
- · Hazard-determining components of labelling:

2-methyl-2H-isothiazol-3-one

· Hazard statements

H317 May cause an allergic skin reaction.

**Precautionary statements** 

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

## SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.
- Dangerous components:

Percentages of the components are expressed as a percentage by weight

CAS: 107-98-2	1-Methoxy-2-propanol	1-10%
EINECS: 203-539-1	♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336	
Index number: 603-064-00-3		
Reg.nr.: 01-2119457435-35		
CAS: 2682-20-4	2-methyl-2H-isothiazol-3-one	<1%
Reg.nr.: 01-2120764690-50	Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400	
	(M=10); Aquatic Chronic 1, H410 (M=1); ♦ Skin Sens. 1A, H317, EUH071	
	Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 %	

Additional information: For the wording of the listed hazard phrases refer to section 16.

# SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

(Contd. on page 3)



Printing date 06.02.2025 Version: 15 (replaces version 14) Revision: 06.02.2025

Trade name: ACRATON WV-HB COATING

(Contd. of page 2)

• 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

### SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- · Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- · 6.2 Environmental precautions:

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· 6.4 Reference to other sections

No dangerous substances are released.

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store material in original, well-closed packages in a cool, well-ventilated area according to local regulations.

- Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Recommended storage temperature: 5 30 °C
- · 7.3 Specific end use(s) No further relevant information available.

### SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

0.1 Control parameters	
Ingredients with limit values that require monitoring at the workplace:	
107-98-2 1-Methoxy-2-propanol	
IOELV Short-term value: 568 mg/m³, 150 ppm Long-term value: 375 mg/m³, 100 ppm Skin	
DNEL (Derived No Effect Level) for workers:	
107-98-2 1-Methoxy-2-propanol	

	-wethoxy-z-propanol	
Dermal	Long-term - systemic effects, worker	50.6 mg/kg bw/day (worker)
Inhalative	Acute - local effects, worker	553.5 mg/m³ (worker)
	Long-term - systemic effects, worker	369 mg/m³ (worker)

(Contd. on page 4)





Printing date 06.02.2025 Version: 15 (replaces version 14) Revision: 06.02.2025

Trade name: ACRATON WV-HB COATING

			(Contd. of page 3)	
· DNEL (De	rived No Effect Level) for the general p	olulatio	n:	
107-98-2 1	I-Methoxy-2-propanol			
Oral	Long-term - systemic effects, general po	pulation	3.3 mg/kg bw/day (general population)	
Dermal	Long-term - systemic effects, general po	pulation	18.1 mg/kg bw/day (general population)	
Inhalative	Long-term - systemic effects, general po	pulation	43.9 mg/m³ (general population)	
· PNEC (Pro	edicted No Effect Concentration) value	s:		
107-98-2 1	I-Methoxy-2-propanol			
Aquatic co	mpartment - freshwater	10 mg/L	(not specified)	
Aquatic co	Aquatic compartment - marine water 1 mg/L (not specified)			
Aquatic co	Aquatic compartment - water, intermittent releases 100 mg/L (not specified)			
Aquatic co	Aquatic compartment - sediment in freshwater 52.3 mg/kg sed dw (not specified)			
Aquatic co	Aquatic compartment - sediment in marine water 5.2 mg/kg sed dw (not specified)			
Terrestrial	compartment - soil	5.49 mg	/kg dw (not specified)	
Sewage tr	Sewage treatment plant 100 mg/L (not specified)		Sewage treatment plant	

· Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne

contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

- Appropriate engineering controls No further data; see section 7.
- Individual protection measures, such as personal protective equipment
- · General protective and hygienic measures:

Provide readily accessible eye wash stations and safety showers.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If

workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed

respirator complying with an approved standard if a risk assessment indicates this is necessary. For organic vapors and solvents type of filter A1 or A2, for dust type of filter P (according to EN 140)

Hand protection



Protective gloves

Chemical resistant gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

#### Penetration time of glove material

KCL Camatril 730 / KCL Dermatril 740

breakthrough time > 480 min.

thickness: 0,4 / 0,11 mm

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Page 5/9



# Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Printing date 06.02.2025 Version: 15 (replaces version 14) Revision: 06.02.2025

Trade name: ACRATON WV-HB COATING

(Contd. of page 4)

· Eye/face protection Goggles recommended during refilling

**Body protection:** 

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved before the product is used by a specialist. If there is a risk of ignition by static electricity, anti-static protective clothing should be worn. For the best

protection against static discharge, clothing should consist of anti-static overalls, boots and gloves. For further information on materials and design requirements and test methods consult the European standard EN 1149.

· Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Liquid

· Colour: According to product specification

Odour: Characteristic
 Odour threshold: Not determined.
 Melting point/freezing point: Undetermined.

Boiling point or initial boiling point and boiling

Boiling point or initial boiling point and boiling

inge 100 °C (7732-18-5 water, distilled, conductivity or of

similar purity)
Not applicable.

· Flammability · Lower and upper explosion limit

Lower: Not determined.

· Upper: Not determined.
· Flash point: Not applicable.
· Decomposition temperature: Not determined.

· pH at 20 °C

· Viscosity:

• Kinematic viscosity at 40 °C: > 20,5 mm<sup>2</sup>/s

· Dynamic at 20 °C: 1,500 mPas

· Solubility

water: Fully miscible.
 Partition coefficient n-octanol/water (log value) Not determined.

• Vapour pressure at 20 °C: 23 hPa (7732-18-5 water, distilled, conductivity or of

similar purity)

· Density and/or relative density

Density at 20 °C:
 Relative density
 Vapour density

Not determined.
Not determined.

9.2 Other information

· Appearance:

· Form: Fluid

Important information on protection of health and

environment, and on safety.

· **Ignition temperature:** Product is not selfigniting.

• **Explosive properties:** Product does not present an explosion hazard.

· Solvent content:

· Water: 8.1 %

· Change in condition · Evaporation rate Not determined.

· Information with regard to physical hazard classes

Explosives Void Flammable gases Void

(Contd. on page 6)



Printing date 06.02.2025 Version: 15 (replaces version 14) Revision: 06.02.2025

Trade name: ACRATON WV-HB COATING

		(Contd. of page
Aerosols	Void	
Oxidising gases	Void	
Gases under pressure	Void	
Flammable liquids	Void	
Flammable solids	Void	
Self-reactive substances and mixtures	Void	
Pyrophoric liquids	Void	
Pyrophoric solids	Void	
Self-heating substances and mixtures	Void	
Substances and mixtures, which emit flamma	able	
gases in contact with water	Void	
Oxidising liquids	Void	
Oxidising solids	Void	
Organic peroxides	Void	
Corrosive to metals	Void	
Desensitised explosives	Void	

# SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC5	0 valu	es relevant for classification:
107-98-2	2 1-Me	thoxy-2-propanol
Oral	LD50	5,660 mg/kg (rat)
Dermal	LD50	13,000 mg/kg (rabbit)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation May cause an allergic skin reaction.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- 11.2 Information on other hazards
- · Endocrine disrupting properties

None of the ingredients is listed.

EU



Printing date 06.02.2025 Version: 15 (replaces version 14) Revision: 06.02.2025

Trade name: ACRATON WV-HB COATING

(Contd. of page 6)

# **SECTION 12: Ecological information**

- · 12.1 Toxicity
- · Aquatic toxicity:

### 107-98-2 1-Methoxy-2-propanol

EC50/48 h 23,300 mg/l (Daphnia magna) LC50/96 h | 6,812 mg/l (Leuciscus idus)

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- · 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

# SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Europear	· European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS	
08 01 00	wastes from MFSU and removal of paint and varnish	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.
- Recommended cleansing agents: Water, if necessary together with cleansing agents.

· 14.1 UN number or ID number		
ADR/RID/ADN, ADN, IMDG, IATA	Void	
14.2 UN proper shipping name		_
ADR/RID/ADN, ADN, IMDG, IATA	Void	
14.3 Transport hazard class(es)		
ADR/RID/ADN, ADN, IMDG, IATA		
Class	Void	
14.4 Packing group		
ADR/RID/ADN, IMDG, IATA	Void	
14.5 Environmental hazards:		
Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	



Printing date 06.02.2025 Version: 15 (replaces version 14) Revision: 06.02.2025

Trade name: ACRATON WV-HB COATING

(Contd. of page 7)

 14.7 Maritime transport in bulk according to IMO instruments

Not applicable.

· UN "Model Regulation": Void

## **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

- **REGULATION (EU) 2019/1148**
- Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

**Annex II - REPORTABLE EXPLOSIVES PRECURSORS** 

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Contact: J. Dijkstra

· Date of previous version: 19.04.2023 · Version number of previous version: 14

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 2: Acute toxicity – Category 2

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

(Contd. on page 9)





Printing date 06.02.2025 Version: 15 (replaces version 14) Revision: 06.02.2025

**Trade name: ACRATON WV-HB COATING** 

(Contd. of page 8)

Skin Sens. 1A: Skin sensitisation – Category 1A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

· Sources

- ECHA European Chemical Agency http://echa.europa.eu/information-on-chemicals
- SDS of raw materials supplied by producer/supplier.
- \* Data compared to the previous version altered.