Printing date 06.02.2025

Version: 39 (replaces version 38)

Revision: 06.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Trade name: <u>ZANDEX ALUMINIUM ZL 105-200</u> · Article number: H14 · UFI: PCUC-Q1E6-X008-7SCP · 1.2 Relevant identified uses of the substance or mixture and uses advised against Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU19 Building and construction work SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC9a Coatings and paints, thinners, paint removers Process category PROC7 Industrial spraying PROC10 Roller application or brushing PROC19 Manual activities involving hand contact PROC13 Treatment of articles by dipping and pouring · Application of the substance / the mixture solvent based, one component cumarone coating 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Zandleven Coatings B.V. Snekertrekweg 57-59, 8912 AA Leeuwarden, Netherlands Tel: +31 58 2129545 Fax: +31 58 2155996 E-mail: info@zandleven.com Internet: www.zandleven.com · Further information obtainable from: R&D department: sds@zandleven.com · 1.4 Emergency telephone number: Nationaal Vergiftigingen Informatie +31 (0)88 755 8000 ORFILA (INRS) : + 33 (0)1 45 42 59 59 Centres Antipoison et de Toxicovigilance ANGERS: 02 41 48 21 21 BORDEAUX: 05 56 96 40 80 LILLE: 0800 59 59 59 LYON: 04 72 11 69 11 MARSEILLE: 04 91 75 25 25 NANCY: 03 83 22 50 50 PARIS: 01 40 05 48 48 STRASBOURG: 03 88 37 37 37 TOULOUSE: 05 61 77 74 47 Giftnotruf der Charité, Berlin: 030/19240 Giftinformationszentrum-Nord der Länder Bremen, Hamburg, Niedersachsen und Schleswig-Holstein (GIZ-Nord) :0551/19 240 Informationszentrale gegen Vergiftungen Zentrum für Kinderheilkunde Universitätsklinikum Bonn: 0228/19240 Giftnotruf Erfurt Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen: 0361/730 730 Informations- und Beratungszentrum für Vergiftungsfälle Klinik für Kinder- und Jugendmedizin Universitätsklinikum des Saarlandes: 06841/19240 Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen - Klinische Toxikologie - Universitätsmedizin der Johannes Gutenberg-Universität Mainz: 06131/19240 Vergiftungs-Informations-Zentrale Zentrum für Kinder- und Jugendmedizin Universitätsklinikum: 0761/19240 Giftnotruf München Toxikologische Abteilung der II. Med. Klinik und Poliklinik: 089/19240 Supplier +31 (0)58 2677590 (during office hours) **SECTION 2: Hazards identification** 

#### · 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

- Skin Irrit. 2 H315 Causes skin irritation.
- Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

(Contd. on page 2)


Printing date 06.02.2025

# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 Version: 39 (replaces version 38)

Revision: 06.02.2025

# Trade name: ZANDEX ALUMINIUM ZL 105-200



· vPvB: Not applicable.

# SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

#### Dangerous components:

Percentages of the components are expressed as a percentage by weight

5 1		
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 128601-23-0 EC number: 918-668-5 Reg.nr.: 01-2119455851-35	C9-aromatics Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Acute Tox. 4, H312; STOT SE 3, H335-H336, EUH066	10-25%
EC number: 919-857-5 Reg.nr.: 01-2119463258-33	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics Flam. Liq. 3, H226; I Asp. Tox. 1, H304; I STOT SE 3, H336, EUH066	2.5-10%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	2.5-10%
• Additional information: For the wording of the listed hazard phrases refer to section 16.		

(Contd. on page 3)

Printing date 06.02.2025

Version: 39 (replaces version 38)

Revision: 06.02.2025

#### Trade name: ZANDEX ALUMINIUM ZL 105-200

(Contd. of page 2)

## **SECTION 4: First aid measures**

- 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately rinse with water.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

### SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### **SECTION 6: Accidental release measures**

- · 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

- Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

## SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- Information about fire and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.
- 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:
- Store material in original, well-closed packages in a cool, well-ventilated area according to local regulations. · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 30 °C
- · 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

FU

Printing date 06.02.2025

Version: 39 (replaces version 38)

Revision: 06.02.2025

(Contd. of page 3)

Trade name: ZANDEX ALUMINIUM ZL 105-200

Ingredien	ol parameters ts with limit values that require monito	oring at the workplace.	
•	-		
1330-20-7 xylene IOELV Short-term value: 442 mg/m³, 100 ppm			
	ong-term value: 221 mg/m³, 50 ppm		
	kin		
	ethylbenzene		
IOELV	nort-term value: 884 mg/m³, 200 ppm ong-term value: 442 mg/m³, 100 ppm		
	kin		
DNEL (De	rived No Effect Level) for workers:		
1330-20-7			
Dermal	Long-term - systemic effects, worker 21	12 mg/kg bw/day (worker)	
		12 mg/m³ (worker)	
		12 mg/m³ (worker)	
	Long-term - systemic effects, worker 22	21 mg/m³ (worker)	
		21 mg/m³ (worker)	
	3-0 C9-aromatics		
Dermal	Long-term - systemic effects, worker 12		
	Long-term - systemic effects, worker 15	51 mg/m³ (human)	
	ethylbenzene		
Dermal	Long-term - systemic effects, worker 18		
Inhalative		93 mg/m³ (worker)	
	Long-term - systemic effects, worker 77		
-	rived No Effect Level) for the general	polulation:	
1330-20-7	-	anulation 10 5 mother buildout (non-one) non-ulation)	
Oral Dermal	Long-term - systemic effects, general po	opulation 12.5 mg/kg bw/day (general population)	
	Acute - systemic effects, general popula		
minalative	Acute - local effects, general population	,	
		opulation 65.3 mg/m <sup>3</sup> (general population)	
	Long-term - local effects, general popula		
128601-23	3-0 C9-aromatics		
Oral	Long-term - systemic effects, general po	opulation 7.5 mg/kg bw/day (human)	
Dermal	Long-term - systemic effects, general po		
Inhalative	Long-term - systemic effects, general po	,	
	ethylbenzene	1	
100 41 4	Long-term - systemic effects, general po	opulation 1.6 mg/kg bw/day (general population)	
	1	opulation 15 mg/m <sup>3</sup> (general population)	
Oral	Long-term - systemic effects, general po	- <u>Farment</u> ( <u>3 F-Far</u> ana)	
Oral Inhalative	Long-term - systemic effects, general po edicted No Effect Concentration) value		
Oral Inhalative	edicted No Effect Concentration) value		
Oral Inhalative <b>PNEC (Pr</b> 1330-20-7	edicted No Effect Concentration) value		
Oral Inhalative <b>PNEC (Pr</b> 1330-20-7 Aquatic co	edicted No Effect Concentration) value xylene	es:	
Oral Inhalative <b>PNEC (Pr</b> 1330-20-7 Aquatic co Aquatic co	edicted No Effect Concentration) value xylene ompartment - freshwater	es: 0.327 mg/L (freshwater) 0.327 mg/L (marine water)	
Oral Inhalative <b>PNEC (Pr</b> <b>1330-20-7</b> Aquatic cc Aquatic cc Aquatic cc Aquatic cc	edicted No Effect Concentration) value xylene ompartment - freshwater ompartment - marine water ompartment - water, intermittent releases ompartment - sediment in freshwater	es: 0.327 mg/L (freshwater) 0.327 mg/L (marine water) 0.327 mg/L (intermittent release water) 12.46 mg/kg sed dw (sediment fresh water)	
Oral Inhalative <b>PNEC (Pr</b> <b>1330-20-7</b> Aquatic co Aquatic co Aquatic co Aquatic co Aquatic co	edicted No Effect Concentration) value xylene ompartment - freshwater ompartment - marine water ompartment - water, intermittent releases	es: 0.327 mg/L (freshwater) 0.327 mg/L (marine water) 0.327 mg/L (intermittent release water)	

Printing date 06.02.2025

Version: 39 (replaces version 38)

Revision: 06.02.2025

### Trade name: ZANDEX ALUMINIUM ZL 105-200

		(Contd. of page 4)
100-41-4 ethylbenzene		
Aquatic compartment - freshwater	0.1 mg/L (not specified)	
Aquatic compartment - marine water	0.01 mg/L (not specified)	
Aquatic compartment - water, intermittent releases	0.1 mg/L (not specified)	
Aquatic compartment - sediment in freshwater	13.7 mg/kg sed dw (not specified)	
Aquatic compartment - sediment in marine water	1.37 mg/kg sed dw (not specified)	
Terrestrial compartment - soil	2.68 mg/kg dw (not specified)	
Sewage treatment plant	9.6 mg/L (not specified)	
Oral secondary poisoning	0.02 mg/kg food (not specified)	

• Additional information: The lists valid during the making were used as basis.

#### · 8.2 Exposure controls

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne

contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. • **Appropriate engineering controls** No further data; see section 7.

Individual protection measures, such as personal protective equipment

#### General protective and hygienic measures:

Provide readily accessible eye wash stations and safety showers.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

#### **Respiratory protection:**

Use suitable respiratory protective device in case of insufficient ventilation.

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If

workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed

respirator complying with an approved standard if a risk assessment indicates this is necessary.

For organic vapors and solvents type of filter A1 or A2, for dust type of filter P (according to EN 140) Hand protection



Protective gloves

Chemical resistant gloves (EN 374)

Check protective gloves prior to each use for their proper condition.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Fluorocarbon rubber (Viton)

Nitrile rubber, NBR

#### Penetration time of glove material

KCL Vitoject 890 breakthrough time > 480 min. thickness: 0,7 mm

at limited contact KCL Camatril 730 breakthrough time 30 min. thickness: 0,4 mm The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

ΕU

Printing date 06.02.2025

# Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 Version: 39 (replaces version 38)

Revision: 06.02.2025

(Contd. of page 5)

## Trade name: ZANDEX ALUMINIUM ZL 105-200

- Not suitable are gloves made of the following materials: All other materials
- Eye/face protection



Tightly sealed goggles

Safety glasses according to EN 166 or equivalent

#### Body protection:

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved before the product is used by a specialist. If there is a risk of ignition by static electricity, anti-static protective clothing should be worn. For the best protection against static discharge, clothing should consist of anti-static overalls, boots and gloves. For further information on materials and design requirements and test methods consult the European standard EN 1149.

#### · Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

## SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties			
· General Information			
· Physical state	Liquid		
· Colour:	According to product specification		
· Odour:	Characteristic		
· Odour threshold:	Not determined.		
<ul> <li>Melting point/freezing point:</li> </ul>	Undetermined.		
Boiling point or initial boiling point and boiling			
range	36 °C (Hydrocarbons, C9-C11, n-alkanes, isoalkanes,		
-	cyclics, < 2% aromatics)		
· Flammability	Flammable.		
• Lower and upper explosion limit			
Lower:	0.7 Vol % (Hydrocarbons, C9, aromatics)		
· Upper:	7.5 Vol % (Hydrocarbons, C9, aromatics)		
Flash point:	30 °C		
• Auto-ignition temperature:	400 °C (7429-90-5 aluminium)		
Decomposition temperature:	Not determined.		
· pH	Not determined.		
· Viscosity:			
· Kinematic viscosity	at 40 °C: > 20,5 mm²/s		
· Dynamic at 20 °C:	100 mPas		
· Solubility			
· water:	Not miscible or difficult to mix.		
<ul> <li>Partition coefficient n-octanol/water (log value)</li> </ul>	Not determined.		
· Vapour pressure at 20 °C:	6.7-8.2 hPa (1330-20-7 xylene)		
Density and/or relative density	· · · · ·		
· Density at 20 °C:	>1.1-<1.1 g/cm <sup>3</sup>		
· Relative density	Not determined.		
· Vapour density	Not determined.		
• 9.2 Other information			
· Appearance:			
· Form:	Fluid		
Important information on protection of health and			
environment, and on safety.			
Ignition temperature:	Product is not selfigniting.		
Explosive properties:	Product is not explosive. However, formation of		
· · ·	explosive air/vapour mixtures are possible.		
	(Contd. on page 7)		

Printing date 06.02.2025

Version: 39 (replaces version 38)

Revision: 06.02.2025

### Trade name: ZANDEX ALUMINIUM ZL 105-200

		(Contd. of page 6)
· Change in condition		
· Evaporation rate	Not determined.	
Information with regard to physical hazard cl	lasses	
Explosives	Void	
· Flammable gases	Void	
Aerosols	Void	
Oxidising gases	Void	
· Gases under pressure	Void	
<sup>·</sup> Flammable liquids	Flammable liquid and vapour.	
· Flammable solids	Void	
Self-reactive substances and mixtures	Void	
· Pyrophoric liquids	Void	
<ul> <li>Pyrophoric solids</li> </ul>	Void	
Self-heating substances and mixtures	Void	
· Substances and mixtures, which emit flamm	able	
gases in contact with water	Void	
· Oxidising liquids	Void	
· Oxidising solids	Void	
<ul> <li>Organic peroxides</li> </ul>	Void	
· Corrosive to metals	Void	
<ul> <li>Desensitised explosives</li> </ul>	Void	

### SECTION 10: Stability and reactivity

• **10.1 Reactivity** No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

• **10.4 Conditions to avoid** No further relevant information available.

• 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

## SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
1330-20	1330-20-7 xylene		
Oral	Oral LD50 3,523 mg/kg (rat)		
Dermal	LD50	2,000 mg/kg (rabbit)	
128601	128601-23-0 C9-aromatics		
Oral	LD50	5,558-7,093 mg/kg (rat)	
Dermal	LD50	2,000-3,160 mg/kg (rabbit)	
Hydroc	Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Oral	LD50	>5,000 mg/kg (rat)	
Dermal	LD50	>5,000 mg/kg (rab)	
100-41-	4 ethy	benzene	
Oral	LD50	3,500 mg/kg (rat)	
Dermal	LD50	17,800 mg/kg (rabbit)	
Primary irritant effect:			
<sup>.</sup> Skin co	rrosio	n/irritation Causes skin irritation.	
· Serious	s eye d	amage/irritation Causes serious eye irritation.	
· Respira	• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.		

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

 $\cdot$  Germ cell mutagenicity Based on available data, the classification criteria are not met.

(Contd. on page 8)

<sup>-</sup> EU

Printing date 06.02.2025

Version: 39 (replaces version 38)

Revision: 06.02.2025

(Contd. of page 7)

## Trade name: ZANDEX ALUMINIUM ZL 105-200

- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards

SECTION 12: Ecological information

- Endocrine disrupting properties
- None of the ingredients is listed.

· 12.1 Toxicity			
Aquatic toxicity:			
1330-20-7 xylene			
EC50/72 h 2.2 mg/l (algae)			
EC50/48 h >3.4 mg/l (Ceriodaphnia dubia)			
LC50/96 h 2.6 mg/l (Oncorhynchus mykiss)			
LC50/24 h 1 mg/l (Daphnia magna)			
100-41-4 ethylbenzene			
EC50/72 h 3.6-4.2 mg/l (algae)			
EC50/24 h 2.2 mg/l (Daphnia magna)			
LC50/96 h 4.2 mg/l (Oncorhynchus mykiss)			
• 12.2 Persistence and degradability No further relevant information available.			
12.3 Bioaccumulative potential No further relevant information available.			
• <b>12.4 Mobility in soil</b> No further relevant information available.			
12.5 Results of PBT and vPvB assessment			
• <b>PBT:</b> Not applicable.			
vPvB: Not applicable.			
12.6 Endocrine disrupting properties			
The product does not contain substances with endocrine disrupting properties.			
12.7 Other adverse effects			
• <b>Remark:</b> Harmful to fish			

· Additional ecological information:

#### · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Harmful to aquatic organisms

## SECTION 13: Disposal considerations

#### · 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· European waste catalogue

		WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS	
	08 01 00	wastes from MFSU and removal of paint and varnish	
	08 01 11*	1* waste paint and varnish containing organic solvents or other hazardous substances	
	HP3	Flammable	
	HP6	6 Acute Toxicity	
	HP14	Ecotoxic	
		(Contd. on norm O)	

(Contd. on page 9)

ĒU

Printing date 06.02.2025

Version: 39 (replaces version 38)

Revision: 06.02.2025

(Contd. of page 8)

Trade name: ZANDEX ALUMINIUM ZL 105-200

· Uncleaned packaging:

• **Recommendation:** Disposal must be made according to official regulations.

SECTION 14: Transport information		
Transport in accordance with ADR/RID, IMDG and ICAO/IATA.		
· 14.1 UN number or ID number · ADR/RID/ADN, IMDG, IATA	UN1263	
<ul> <li>14.2 UN proper shipping name</li> <li>ADR/RID/ADN</li> <li>IMDG, IATA</li> </ul>	1263 PAINT PAINT	
· 14.3 Transport hazard class(es)		
· ADR/RID/ADN, IMDG, IATA		
Class	3 Flammable liquids.	
· Label	3	
<ul> <li>14.4 Packing group</li> <li>ADR/RID/ADN, IMDG, IATA</li> </ul>	111	
· 14.5 Environmental hazards: · Marine pollutant:	No	
<ul> <li>14.6 Special precautions for user</li> <li>Hazard identification number (Kemler code):</li> <li>EMS Number:</li> <li>Stowage Category</li> </ul>	Warning: Flammable liquids. 30 F-E, <u>S-E</u> A	
· 14.7 Maritime transport in bulk according to IM	0	
instruments	Not applicable.	
· Transport/Additional information:		
<ul> <li>ADR/RID/ADN</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml	
<ul> <li>Transport category</li> <li>Tunnel restriction code</li> </ul>	3 D/E	
<ul> <li>IMDG</li> <li>Limited quantities (LQ)</li> <li>Excepted quantities (EQ)</li> </ul>	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml	
· UN "Model Regulation":	UN 1263 PAINT, 3, III	

## SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

(Contd. on page 10)

<sup>——</sup> EU

Printing date 06.02.2025

Version: 39 (replaces version 38)

Revision: 06.02.2025

(Contd. of page 9)

3

3

Trade name: ZANDEX ALUMINIUM ZL 105-200

• Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t • Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

### **REGULATION (EU) 2019/1148**

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

#### Regulation (EC) No 273/2004 on drug precursors

108-88-3 toluene

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

108-88-3 toluene

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Classification according to Regulation (EC) No 1272/2008 The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008. · Contact: J. Dijkstra Date of previous version: 19.04.2023 Version number of previous version: 38

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 2: Flammable liquids Category 2 Flam. Liq. 3: Flammable liquids Category 3
- Acute Tox. 4: Acute toxicity Category 4 Skin Irrit. 2: Skin corrosion/irritation Category 2
- Eye Irrit. 2: Serious eye damage/eye irritation Category 2
- STOT SE 3: Specific target organ toxicity (single exposure) Category 3
- STOT RE 2: Specific target organ toxicity (repeated exposure) Category 2 Asp. Tox. 1: Aspiration hazard Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Sources

- ECHA European Chemical Agency http://echa.europa.eu/information-on-chemicals
- SDS of raw materials supplied by producer/supplier.
- \* Data compared to the previous version altered.