Printing date 06.02.2025

Version: 13 (replaces version 12)

Revision: 06.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Trade name: <u>2 V 37 VERHARDER</u> · Article number: 2V37 · UFI: XNUS-U0QF-900H-65YK · 1.2 Relevant identified uses of the substance or mixture and uses advised against Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU19 Building and construction work SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC9a Coatings and paints, thinners, paint removers Process category PROC7 Industrial spraying PROC10 Roller application or brushing PROC19 Manual activities involving hand contact PROC13 Treatment of articles by dipping and pouring · Application of the substance / the mixture solvent based, two component epoxy coating hardener 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Zandleven Coatings B.V. Snekertrekweg 57-59, 8912 AA Leeuwarden, Netherlands Tel: +31 58 2129545 Fax: +31 58 2155996 E-mail: info@zandleven.com Internet: www.zandleven.com · Further information obtainable from: R&D department: sds@zandleven.com · 1.4 Emergency telephone number: Nationaal Vergiftigingen Informatie +31 (0)88 755 8000 ORFILA (INRS) : + 33 (0)1 45 42 59 59 Centres Antipoison et de Toxicovigilance ANGERS: 02 41 48 21 21 BORDEAUX: 05 56 96 40 80 LILLE: 0800 59 59 59 LYON: 04 72 11 69 11 MARSEILLE: 04 91 75 25 25 NANCY: 03 83 22 50 50 PARIS: 01 40 05 48 48 STRASBOURG: 03 88 37 37 37 TOULOUSE: 05 61 77 74 47 Giftnotruf der Charité, Berlin: 030/19240 Giftinformationszentrum-Nord der Länder Bremen, Hamburg, Niedersachsen und Schleswig-Holstein (GIZ-Nord) :0551/19 240 Informationszentrale gegen Vergiftungen Zentrum für Kinderheilkunde Universitätsklinikum Bonn: 0228/19240 Giftnotruf Erfurt Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen: 0361/730 730 Informations- und Beratungszentrum für Vergiftungsfälle Klinik für Kinder- und Jugendmedizin Universitätsklinikum des Saarlandes: 06841/19240 Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen - Klinische Toxikologie - Universitätsmedizin der Johannes Gutenberg-Universität Mainz: 06131/19240 Vergiftungs-Informations-Zentrale Zentrum für Kinder- und Jugendmedizin Universitätsklinikum: 0761/19240 Giftnotruf München Toxikologische Abteilung der II. Med. Klinik und Poliklinik: 089/19240 Supplier +31 (0)58 2677590 (during office hours)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Dam. 1 H318 Causes serious eye damage.


Skin Sens. 1 H317 May cause an allergic skin reaction.

Printing date 06.02.2025

Version: 13 (replaces version 12)

Revision: 06.02.2025

Trade name: 2 V 37 VERHARDER



SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

Percentages of the components are expressed as a percentage by weight

CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	10-25%
CAS: 100-41-4 EINECS: 202-849-4 Index number: 601-023-00-4 Reg.nr.: 01-2119489370-35	ethylbenzene Flam. Liq. 2, H225; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H332; Aquatic Chronic 3, H412	2.5-10%
	triethyleentetramine Skin Corr. 1B, H314; O Acute Tox. 4, H312; Skin Sens. 1, H317; Aquatic Chronic 3, H412	2.5-10%
• Additional information: For the wording of the listed hazard phrases refer to section 16.		

(Contd. on page 3)

Printing date 06.02.2025

Version: 13 (replaces version 12)

Revision: 06.02.2025

Trade name: 2 V 37 VERHARDER

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- After inhalation:
- Supply fresh air and to be sure call for a doctor.
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent.

Dispose contaminated material as waste according to section 13.

- Ensure adequate ventilation.
- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling
- Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.
- **Information about fire and explosion protection:** Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

• 7.2 Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles:

Store material in original, well-closed packages in a cool, well-ventilated area according to local regulations. Information about storage in one common storage facility: Not required.

- Further information about storage conditions: Keep container tightly sealed.
- · Recommended storage temperature: 5 30 °C

(Contd. on page 4)

EU

Printing date 06.02.2025

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version: 13 (replaces version 12)

Revision: 06.02.2025

(Contd. of page 3)

Trade name: 2 V 37 VERHARDER

· 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: 				
1330-20-	-	into inig at t		
	hort-term value: 442 mg/m³, 100 ppm			
	ong-term value: 221 mg/m³, 50 ppm			
	kin			
100-41-4	ethylbenzene			
	hort-term value: 884 mg/m³, 200 ppm			
	ong-term value: 442 mg/m³, 100 ppm			
	kin			
•	erived No Effect Level) for workers:			
1330-20-	-			
Dermal	Long-term - systemic effects, worker			
Inhalative	Acute - systemic effects, worker	442 mg/m ³		
	Acute - local effects, worker	442 mg/m ³	(worker)	
	Long-term - systemic effects, worker	221 mg/m ³	(worker)	
	Long-term - local effects, worker	221 mg/m ³	(worker)	
100-41-4	ethylbenzene			
Dermal	Long-term - systemic effects, worker	180 mg/kg	bw/day (worker)	
Inhalative	Acute - local effects, worker	293 mg/m ³	(worker)	
	Long-term - systemic effects, worker	77 mg/m³ (worker)	
· DNEL (D	erived No Effect Level) for the gener	al polulatio	n:	
1330-20-	· •			
Oral	-	population	12.5 mg/kg bw/day (general population)	
Dermal			125 mg/kg bw/day (general population)	
Inhalative	Acute - systemic effects, general population		260 mg/m ³ (general population)	
	Acute - local effects, general population		260 mg/m³ (general population)	
	Long-term - systemic effects, general population		65.3 mg/m ³ (general population)	
	Long-term - local effects, general pop		65.3 mg/m ³ (general population)	
100-41-4	ethylbenzene			
Oral	•	Dopulation	1.6 mg/kg bw/day (general population)	
-	Long-term - systemic effects, general			
	redicted No Effect Concentration) va	· ·	······································	
1330-20-	,	liues.		
	ompartment - freshwater	0 327 m	ng/L (freshwater)	
			0.327 mg/L (freshwater)	
Aquatic compartment - marine water			0.327 mg/L (marine water)	
Aquatic compartment - water, intermittent releases				
-	Aquatic compartment - sediment in freshwater		12.46 mg/kg sed dw (sediment fresh water)	
			12.46 mg/kg sed dw (sediment marine water)	
-		-	2.31 mg/kg dw (soil) 6.58 mg/L (sewage treatment plant)	
•	- · · ·		i/L (sewage treatment plant)	
100-41-4 ethylbenzene		0.1 m=/	0.4 mm/l (not on optical)	
		•	0.1 mg/L (not specified)	
Aquatic compartment - marine water		-	0.01 mg/L (not specified)	
Aquatic compartment - water, intermittent releases		•		
Aquatic compartment - sediment in freshwater Aquatic compartment - sediment in marine water		-	y/kg sed dw (not specified) y/kg sed dw (not specified)	
A				

EU

Printing date 06.02.2025

Version: 13 (replaces version 12)

Revision: 06.02.2025

-1

de name: 2 V 37 VERHARDER		
	(Contd. of page 4	
Terrestrial compartment - soil	2.68 mg/kg dw (not specified)	
Sewage treatment plant	9.6 mg/L (not specified)	
Oral secondary poisoning	0.02 mg/kg food (not specified)	
 Additional information: The lists valid du 	ring the making were used as basis.	
controls to keep worker exposure to airbor contaminants below any recommended or vapour or dust concentrations below any lo Appropriate engineering controls No fur Individual protection measures, such as General protective and hygienic measure Provide readily accessible eye wash statio Keep away from foodstuffs, beverages and Immediately remove all soiled and contam Wash hands before breaks and at the end Avoid contact with the skin. Avoid contact with the skin. Respiratory protection: In case of brief exposure or low pollution u use self-contained respiratory protective d Respirator selection must be based on kno the safe working limits of the selected resp workers are exposed to concentrations ab respirator complying with an approved station	 statutory limits. The engineering controls also need to keep gas, ower explosive limits. Use explosion-proof ventilation equipment. rther data; see section 7. s personal protective equipment res: ons and safety showers. d feed. iniated clothing d of work. use respiratory filter device. In case of intensive or longer exposure levice. own or anticipated exposure levels, the hazards of the product and birator. If ove the exposure limit, they must use appropriate, certified	
Protective gloves		
Chemical resistant gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves		
The selection of the suitable gloves does r and varies from manufacturer to manufact	not only depend on the material, but also on further marks of quality curer. As the product is a preparation of several substances, the e calculated in advance and has therefore to be checked prior to the	

· Penetration time of glove material KCL Vitoject 890

breakthrough time > 480 min. thickness: 0,7 mm

at limited contact KCL Camatril 730 breakthrough time 30 min. thickness: 0,4 mm The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. · Not suitable are gloves made of the following materials: All other materials

(Contd. on page 6)

EU

Printing date 06.02.2025

Version: 13 (replaces version 12)

Revision: 06.02.2025

Trade name: 2 V 37 VERHARDER

(Contd. of page 5)

Tightly sealed goggles

Safety glasses according to EN 166 or equivalent

Body protection:

· Eye/face protection

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved before the product is used by a specialist.

If there is a risk of ignition by static electricity, anti-static protective clothing should be worn. For the best protection against static discharge, clothing should consist of anti-static overalls, boots and gloves. For further information on materials and design requirements and test methods consult the European standard EN 1149.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties		
General Information		
· Physical state	Liquid	
· Colour:	According to product specification	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
Melting point/freezing point:	Undetermined.	
Boiling point or initial boiling point and boiling		
range	116-118 °C (71-36-3 butan-1-ol)	
Flammability	Flammable.	
Lower and upper explosion limit		
Lower:	1.5 Vol % (71-36-3 butan-1-ol)	
Upper:	9.4 Vol % (71-36-3 butan-1-ol)	
Flash point:	35 °C	
Auto-ignition temperature:	340 °C (71-36-3 butan-1-ol)	
Decomposition temperature:	Not determined.	
pH	Not determined.	
Viscosity:		
Kinematic viscosity	at 40 °C: > 20,5 mm²/s	
Dynamic at 20 °C:	5,500 mPas	
Solubility		
water:	Not miscible or difficult to mix.	
Partition coefficient n-octanol/water (log value)	Not determined.	
Vapour pressure at 20 °C:	10 hPa (71-36-3 butan-1-ol)	
Density and/or relative density		
Density at 20 °C:	0.96 g/cm³	
Relative density	Not determined.	
Vapour density	Not determined.	
9.2 Other information		
Appearance:		
Form:	Fluid	
Important information on protection of health and		
environment, and on safety.		
Ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product is not explosive. However, formation of	
	explosive air/vapour mixtures are possible.	

Printing date 06.02.2025

Version: 13 (replaces version 12)

Revision: 06.02.2025

Trade name: 2 V 37 VERHARDER

		(Contd. of page 6)	
· Change in condition			
· Evaporation rate	Not determined.		
· Information with regard to physical hazard classes			
Explosives	Void		
· Flammable gases	Void		
Aerosols	Void		
· Oxidising gases	Void		
· Gases under pressure	Void		
· Flammable liquids	Flammable liquid and vapour.		
· Flammable solids	Void		
 Self-reactive substances and mixtures 	Void		
· Pyrophoric liquids	Void		
· Pyrophoric solids	Void		
 Self-heating substances and mixtures 	Void		
· Substances and mixtures, which emit flamm	able		
gases in contact with water	Void		
· Oxidising liquids	Void		
· Oxidising solids	Void		
· Organic peroxides	Void		
· Corrosive to metals	Void		
· Desensitised explosives	Void		

SECTION 10: Stability and reactivity

· **10.1 Reactivity** No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

10.3 Possibility of hazardous reactions No dangerous reactions known.

• **10.4 Conditions to avoid** No further relevant information available.

· 10.5 Incompatible materials: No further relevant information available.

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:			
1330-20	1330-20-7 xylene		
Oral	LD50	3,523 mg/kg (rat)	
Dermal	LD50	2,000 mg/kg (rabbit)	
100-41-	4 ethy	Ibenzene	
Oral	LD50	3,500 mg/kg (rat)	
Dermal	LD50	17,800 mg/kg (rabbit)	
triethyle	triethyleentetramine		
Oral	LD50	2,500 mg/kg (rat)	
Dermal	LD50	805 mg/kg (rabbit)	
· Primary	Primary irritant effect:		
Skin co	· Skin corrosion/irritation Causes skin irritation.		
· Serious	· Serious eye damage/irritation Causes serious eye damage.		
Respiratory or skin sensitisation May cause an allergic skin reaction.			
Germ cell mutagenicity Based on available data, the classification criteria are not met.			
· Carcino	· Carcinogenicity Based on available data, the classification criteria are not met.		
· Reprod	Reproductive toxicity Based on available data, the classification criteria are not met.		
· STOT-s	· STOT-single exposure May cause respiratory irritation		

STOT-single exposure May cause respiratory irritation.
 STOT-repeated exposure Based on available data, the classification criteria are not met.

(Contd. on page 8)

EU

Printing date 06.02.2025

Version: 13 (replaces version 12)

Revision: 06.02.2025

(Contd. of page 7)

Trade name: 2 V 37 VERHARDER

· Aspiration hazard Based on available data, the classification criteria are not met.

11.2 Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity:
- 1330-20-7 xylene
- EC50/72 h 2.2 mg/l (algae)
- EC50/48 h >3.4 mg/l (Ceriodaphnia dubia)
- LC50/96 h 2.6 mg/l (Oncorhynchus mykiss)

LC50/24 h 1 mg/l (Daphnia magna)

100-41-4 ethylbenzene

EC50/72 h 3.6-4.2 mg/l (algae)

EC50/24 h 2.2 mg/l (Daphnia magna)

LC50/96 h 4.2 mg/l (Oncorhynchus mykiss)

- · 12.2 Persistence and degradability No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Must not reach sewage water or drainage ditch undiluted or unneutralised. Danger to drinking water if even small quantities leak into the ground.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European waste catalogue

Luiopean	European waste catalogue	
08 00 00	WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS	
08 01 00	wastes from MFSU and removal of paint and varnish	
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	
HP3	Flammable	
HP4	Irritant - skin irritation and eye damage	
HP5	Specific Target Organ Toxicity (STOT)/Aspiration Toxicity	
HP6	Acute Toxicity	

(Contd. on page 9)

Printing date 06.02.2025

Version: 13 (replaces version 12)

Revision: 06.02.2025

(Contd. of page 8)

Trade name: 2 V 37 VERHARDER

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

Transport in accordance with ADR/RID, IMDG and ICAO/IATA. 14.1 UN number or ID number ADR/RID/ADN, ADN, IMDG Void IATA UN1263 14.2 UN proper shipping name ADR/RID/ADN, ADN, IMDG Void IATA PAINT 14.3 Transport hazard class(es) ADR/RID/ADN, ADN, IMDG Class Void IATA Void IATA PAINT 14.3 Transport hazard class(es) ADR/RID/ADN, ADN, IMDG Class Void IATA Void IATA Void IATA Void IATA Void IATA Void 14.4 Packing group ADR/RID/ADN, IMDG Void IATA III 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Maritime transport in bulk according to	SECTION 14: Transport information		
ADR/RID/ADN, ADN, IMDG Void IATA UN1263 14.2 UN proper shipping name ADR/RID/ADN, ADN, IMDG ADR/RID/ADN, ADN, IMDG Void IATA PAINT 14.3 Transport hazard class(es) ADR/RID/ADN, ADN, IMDG Class Void IATA Void IATA Void Class Void IATA Void IATA Void Class Void IATA III 14.4 Packing group ADR/RID/ADN, IMDG ADR/RID/ADN, IMDG Void IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Maritime transport in bulk according to IMO instruments Not applicable. 14.7 Maritime transport Additional information:	Transport in accordance with ADR/RID, IMDG and ICAO/IATA.		
ADR/RID/ADN, ADN, IMDG Void 1ATA PAINT 14TA PAINT 14TA PAINT 14TA PAINT 14TA Void Class Void IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Maritime transport in bulk according to IMO instruments Not applicable. 1Transport/Additional information: Void Void Void Void Void Void Void ADN (ADN) Remarks:	ADR/RID/ADN, ADN, IMDG		
ADR/RID/ADN, ADN, IMDG Class Void IATA ADR/RID/ADN, IMDG Void IATA III 14.5 Environmental hazards: Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Maritime transport in bulk according to IMO instruments Not applicable. 1Transport/Additional information: ADR/RID/ADN Remarks: Up to 450 litre exempted according to ADR 2.2.3.1.5. IMDG Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. IATA The "viscosity exemption" provisions do NOT apply to air transport.	ADR/RID/ADN, ADN, IMDG		
Class Void IATA IATA IATA IATA IATA III Class 3 Flammable liquids. Label 3 14.4 Packing group Jata ADR/RID/ADN, IMDG Void IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: ADR/RID/ADN Remarks: Up to 450 litre exempted according to ADR 2.2.3.1.5. IMDG Remarks: Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. IATA The "viscosity exemption" provisions do NOT apply to air transport.	 14.3 Transport hazard class(es) 		
Class Class Class S Flammable liquids. S Flammable liquids.	Class	Void	
Label 3 14.4 Packing group Void ADR/RID/ADN, IMDG Void IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: ADR/RID/ADN Remarks: Up to 450 litre exempted according to ADR 2.2.3.1.5. IMDG Remarks: IMDG Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. IATA The "viscosity exemption" provisions do NOT apply to air transport.	IATA		
Label 3 14.4 Packing group Void ADR/RID/ADN, IMDG Void IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: ADR/RID/ADN Remarks: Up to 450 litre exempted according to ADR 2.2.3.1.5. IMDG Remarks: IMDG Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. IATA The "viscosity exemption" provisions do NOT apply to air transport.			
14.4 Packing group Void ADR/RID/ADN, IMDG Void IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: ADR/RID/ADN Remarks: Up to 450 litre exempted according to ADR 2.2.3.1.5. IMDG Remarks: Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. IATA The "viscosity exemption" provisions do NOT apply to air transport.			
ADR/RID/ADN, IMDG Void IATA III 14.5 Environmental hazards: No Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: Not applicable. ADR/RID/ADN Up to 450 litre exempted according to ADR 2.2.3.1.5. IMDG Remarks: Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. IATA The "viscosity exemption" provisions do NOT apply to air transport.		3	
Marine pollutant: No 14.6 Special precautions for user Not applicable. 14.7 Maritime transport in bulk according to IMO instruments Not applicable. Transport/Additional information: Not applicable. ADR/RID/ADN Up to 450 litre exempted according to ADR 2.2.3.1.5. IMDG Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. IATA The "viscosity exemption" provisions do NOT apply to air transport.	· ADR/RID/ADN, IMDG		
14.7 Maritime transport in bulk according to IMO instruments Not applicable. 17ransport/Additional information: ADR/RID/ADN ADR/RID/ADN Up to 450 litre exempted according to ADR 2.2.3.1.5. IMDG Remarks: Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. IATA The "viscosity exemption" provisions do NOT apply to air transport.		No	
instruments Not applicable. Transport/Additional information: ADR/RID/ADN ADR/RID/ADN Up to 450 litre exempted according to ADR 2.2.3.1.5. IMDG Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. IATA The "viscosity exemption" provisions do NOT apply to air transport.	 14.6 Special precautions for user 	Not applicable.	
ADR/RID/ADN Remarks: Up to 450 litre exempted according to ADR 2.2.3.1.5. IMDG Remarks: Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. IATA Remarks: The "viscosity exemption" provisions do NOT apply to air transport.			
• Remarks: Up to 450 litre exempted according to ADR 2.2.3.1.5. • IMDG • Remarks: • IATA • Remarks: • Remarks: The "viscosity exemption" provisions do NOT apply to air transport.	• Transport/Additional information:		
IMDG Remarks: Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. IATA Remarks: The "viscosity exemption" provisions do NOT apply to air transport.	· ADR/RID/ADN		
• Remarks: Up to 450 litre: Transport in accordance with Packs 2.3.2.5 of the IMDG Code. • IATA • Remarks: The "viscosity exemption" provisions do NOT apply to air transport.	· Remarks:	Up to 450 litre exempted according to ADR 2.2.3.1.5.	
• Remarks: The "viscosity exemption" provisions do NOT apply to air transport.			
· UN "Model Regulation": Void			
	· UN "Model Regulation":	Void	

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

· Seveso category P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

(Contd. on page 10)

- EU

Printing date 06.02.2025

Version: 13 (replaces version 12)

Revision: 06.02.2025

(Contd. of page 9)

Trade name: 2 V 37 VERHARDER

• Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment - Annex II

None of the ingredients is listed.

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Contact: J. Dijkstra

Date of previous version: 20.04.2023

- · Version number of previous version: 12

· Abbreviations and acronyms: ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) DNEL: Derived No-Effect Level (REACH) PNEC: Predicted No-Effect Concentration (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - Category 4 Skin Corr. 1B: Skin corrosion/irritation - Category 1B Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2 Skin Sens. 1: Skin sensitisation – Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Sources

ECHA European Chemical Agency - http://echa.europa.eu/information-on-chemicals

- SDS of raw materials supplied by producer/supplier.
- ** Data compared to the previous version altered.

FII