Printing date 06.02.2025

Version: 26 (replaces version 25)

Revision: 06.02.2025

SECTION 1: Identification of the substance/mixture and of the company/undertaking 1.1 Product identifier Trade name: <u>ZINKSILICAAT ZL 400-55 PASTA</u> · Article number: C31PASTA · UFI: 0SC0-30TK-1007-AR8A · 1.2 Relevant identified uses of the substance or mixture and uses advised against Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites SU19 Building and construction work SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen) · Product category PC9a Coatings and paints, thinners, paint removers Process category PROC7 Industrial spraying PROC10 Roller application or brushing PROC19 Manual activities involving hand contact PROC13 Treatment of articles by dipping and pouring · Application of the substance / the mixture solvent based, two component ethyl silicate zinc paste 1.3 Details of the supplier of the safety data sheet · Manufacturer/Supplier: Zandleven Coatings B.V. Snekertrekweg 57-59, 8912 AA Leeuwarden, Netherlands Tel: +31 58 2129545 Fax: +31 58 2155996 E-mail: info@zandleven.com Internet: www.zandleven.com · Further information obtainable from: R&D department: sds@zandleven.com · 1.4 Emergency telephone number: Nationaal Vergiftigingen Informatie +31 (0)88 755 8000 ORFILA (INRS) : + 33 (0)1 45 42 59 59 Centres Antipoison et de Toxicovigilance ANGERS: 02 41 48 21 21 BORDEAUX: 05 56 96 40 80 LILLE: 0800 59 59 59 LYON: 04 72 11 69 11 MARSEILLE: 04 91 75 25 25 NANCY: 03 83 22 50 50 PARIS: 01 40 05 48 48 STRASBOURG: 03 88 37 37 37 TOULOUSE: 05 61 77 74 47 Giftnotruf der Charité, Berlin: 030/19240 Giftinformationszentrum-Nord der Länder Bremen, Hamburg, Niedersachsen und Schleswig-Holstein (GIZ-Nord) :0551/19 240 Informationszentrale gegen Vergiftungen Zentrum für Kinderheilkunde Universitätsklinikum Bonn: 0228/19240 Giftnotruf Erfurt Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen: 0361/730 730 Informations- und Beratungszentrum für Vergiftungsfälle Klinik für Kinder- und Jugendmedizin Universitätsklinikum des Saarlandes: 06841/19240 Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen - Klinische Toxikologie - Universitätsmedizin der Johannes Gutenberg-Universität Mainz: 06131/19240 Vergiftungs-Informations-Zentrale Zentrum für Kinder- und Jugendmedizin Universitätsklinikum: 0761/19240 Giftnotruf München Toxikologische Abteilung der II. Med. Klinik und Poliklinik: 089/19240 Supplier +31 (0)58 2677590 (during office hours)

SECTION 2: Hazards identification

· 2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

Flam. Liq. 3 H226 Flammable liquid and vapour.

Aquatic Acute 1 H400 Very toxic to aquatic life.

Aquatic Chronic 1 H410 Very toxic to aquatic life with long lasting effects.

(Contd. on page 2)

EU


Printing date 06.02.2025

Safety data sheet

according to Regulation (EC) No 1907/2006, Article 31 Version: 26 (replaces version 25)

Revision: 06.02.2025

_ . _.....



SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:

Percentages of the components are expressed as a percentage by weight

| 5 | | |
|---|---|---------|
| CAS: 7440-66-6 EINECS: 231-175-3 Index number: 030-001-01-9 Reg.nr.: 01-2119467174-37-xxxx | zinc powder -zinc dust (stabilized) Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | 75-100% |
| CAS: 107-98-2 EINECS: 203-539-1 Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35 | 1-Methoxy-2-propanol | 2.5-10% |
| CAS: 1314-13-2 EINECS: 215-222-5 Index number: 030-013-00-7 Reg.nr.: 01-2119463881-32 | Zinc oxide Aquatic Acute 1, H400; Aquatic Chronic 1, H410 | 2.5-10% |
| CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32 | xylene Flam. Liq. 3, H226; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 | 2.5-10% |
| • Additional information: For the | wording of the listed hazard phrases refer to section 16. | ı |

SECTION 4: First aid measures

· 4.1 Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

EU -

Printing date 06.02.2025

Version: 26 (replaces version 25)

Revision: 06.02.2025

Trade name: ZINKSILICAAT ZL 400-55 PASTA

(Contd. of page 2)

- After inhalation: Supply fresh air; consult doctor in case of complaints. • After skin contact: Immediately rinse with water.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed
- No further relevant information available.
- 4.3 Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:
- CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- 6.3 Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13. Ensure adequate ventilation.

- 6.4 Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling Use only in well ventilated areas.
- Information about fire and explosion protection:
- Keep ignition sources away Do not smoke.
- Protect against electrostatic charges.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store material in original, well-closed packages in a cool, well-ventilated area according to local regulations. Information about storage in one common storage facility: Not required.

- Further information about storage conditions: Keep container tightly sealed.
- Recommended storage temperature: 5 30 °C
- 7.3 Specific end use(s) No further relevant information available.

(Contd. on page 4)

FU

Printing date 06.02.2025

Version: 26 (replaces version 25)

Revision: 06.02.2025

(Contd. of page 3)

Trade name: ZINKSILICAAT ZL 400-55 PASTA

| 8.1 Contro | ol parameters | | |
|------------|---|-----------------------|--|
| | ts with limit values that require mor | nitoring at t | he workplace: |
| - | | | · · |
| IOELV Sh | ort-term value: 568 mg/m³, 150 ppm | | |
| Lo | ng-term value: 375 mg/m³, 100 ppm | | |
| 1330-20-7 | | | |
| | ort-term value: 442 mg/m³, 100 ppm | | |
| | ng-term value: 221 mg/m³, 50 ppm | | |
| Sk | in | | |
| DNEL (De | rived No Effect Level) for workers: | | |
| 7440-66-6 | zinc powder -zinc dust (stabilized) | | |
| Dermal | Long-term - systemic effects, worker | | |
| | Long-term - systemic effects, worker | 5 mg/m³ (w | orker) |
| | I-Methoxy-2-propanol | | |
| Dermal | Long-term - systemic effects, worker | | |
| Inhalative | Acute - local effects, worker | 553.5 mg/n | |
| 4044 40 0 | Long-term - systemic effects, worker | 369 mg/m ³ | (worker) |
| | Zinc oxide | | |
| Dermal | Long-term - systemic effects, worker | | |
| 1330-20-7 | Long-term - systemic effects, worker | 5 mg/m² (w | orker) |
| Dermal | Long-term - systemic effects, worker | 212 mg/kg | hu/dov (worker) |
| | Acute - systemic effects, worker | 442 mg/m ³ | , |
| IIIIaiauve | Acute - local effects, worker | 442 mg/m ³ | . , |
| | Long-term - systemic effects, worker | | |
| | Long-term - local effects, worker | 221 mg/m ³ | |
| | rived No Effect Level) for the gener | - | · , |
| • | zinc powder -zinc dust (stabilized) | • | 11: |
| Oral | | | 0.83 mg/kg bw/day (general population) |
| Dermal | | | 83 mg/kg bw/day (general population) |
| | Long-term - systemic effects, general | | |
| | I-Methoxy-2-propanol | population | |
| Oral | | l population | 3.3 mg/kg bw/day (general population) |
| Dermal | | | 18.1 mg/kg bw/day (general population) |
| | Long-term - systemic effects, general | | |
| | Zinc oxide | | |
| Oral | | l population | 0.83 mg/kg bw/day (general population) |
| Dermal | | | 83 mg/kg bw/day (general population) |
| Inhalative | Long-term - systemic effects, general | l population | 2.5 mg/m³ (general population) |
| 1330-20-7 | | | |
| Oral | - | l population | 12.5 mg/kg bw/day (general population) |
| Dermal | Long-term - systemic effects, genera | l population | 125 mg/kg bw/day (general population) |
| Inhalative | Acute - systemic effects, general pop | oulation | 260 mg/m³ (general population) |
| | Acute - local effects, general populati | ion | 260 mg/m³ (general population) |
| | Long-term - systemic effects, genera | l population | 65.3 mg/m³ (general population) |
| | Long-term - local effects, general pop | | 65.3 mg/m³ (general population) |

Printing date 06.02.2025

Version: 26 (replaces version 25)

Revision: 06.02.2025

Trade name: ZINKSILICAAT ZL 400-55 PASTA

| PNEC (Predicted No Effect Concentration) value | (Contd. of pa |
|--|--|
| 7440-66-6 zinc powder -zinc dust (stabilized) | |
| Aquatic compartment - freshwater | 0.0206 mg/L (not specified) |
| Aquatic compartment - marine water | 0.0061 mg/L (not specified) |
| Aquatic compartment - sediment in freshwater | 117.8 mg/kg sed dw (not specified) |
| Aquatic compartment - sediment in marine water | 56.5 mg/kg sed dw (not specified) |
| Terrestrial compartment - soil | 35.6 mg/kg dw (not specified) |
| Sewage treatment plant | 0.1 mg/L (not specified) |
| 107-98-2 1-Methoxy-2-propanol | |
| Aquatic compartment - freshwater | 10 mg/L (not specified) |
| Aquatic compartment - marine water | 1 mg/L (not specified) |
| Aquatic compartment - water, intermittent releases | 100 mg/L (not specified) |
| Aquatic compartment - sediment in freshwater | 52.3 mg/kg sed dw (not specified) |
| Aquatic compartment - sediment in marine water | 5.2 mg/kg sed dw (not specified) |
| Terrestrial compartment - soil | 5.49 mg/kg dw (not specified) |
| Sewage treatment plant | 100 mg/L (not specified) |
| 1314-13-2 Zinc oxide | |
| Aquatic compartment - freshwater | 0.0206 mg/L (not specified) |
| Aquatic compartment - marine water | 0.0061 mg/L (not specified) |
| Aquatic compartment - sediment in freshwater | 117.8 mg/kg sed dw (not specified) |
| Aquatic compartment - sediment in marine water | 56.5 mg/kg sed dw (not specified) |
| Terrestrial compartment - soil | 35.6 mg/kg dw (not specified) |
| Sewage treatment plant | 0.1 mg/L (not specified) |
| 1330-20-7 xylene | |
| Aquatic compartment - freshwater | 0.327 mg/L (freshwater) |
| Aquatic compartment - marine water | 0.327 mg/L (marine water) |
| Aquatic compartment - water, intermittent releases | 0.327 mg/L (intermittent release water) |
| Aquatic compartment - sediment in freshwater | 12.46 mg/kg sed dw (sediment fresh water) |
| Aquatic compartment - sediment in marine water | 12.46 mg/kg sed dw (sediment marine water) |
| Terrestrial compartment - soil | 2.31 mg/kg dw (soil) |
| Sewage treatment plant | 6.58 mg/L (sewage treatment plant) |
| Additional information: The lists valid during the r | naking were used as basis. |

Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne

contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment. • **Appropriate engineering controls** No further data; see section 7.

Individual protection measures, such as personal protective equipment

• General protective and hygienic measures:

Provide readily accessible eye wash stations and safety showers.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work. **Respiratory protection:**

Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified

workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed

respirator complying with an approved standard if a risk assessment indicates this is necessary.

For organic vapors and solvents type of filter A1 or A2, for dust type of filter P (according to EN 140)

(Contd. on page 6)

Printing date 06.02.2025

Version: 26 (replaces version 25)

Revision: 06.02.2025

Trade name: ZINKSILICAAT ZL 400-55 PASTA

(Contd. of page 5) Hand protection Protective gloves Chemical resistant gloves (EN 374) Check protective gloves prior to each use for their proper condition. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. Fluorocarbon rubber (Viton) Nitrile rubber, NBR · Penetration time of glove material KCL Camatril 730 / Best Nitri-solve 730 breakthrough time > 480 min. thickness: 0,4 / 0,38 mm The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed. Not suitable are gloves made of the following materials: Neoprene gloves Disposables Eye/face protection Tightly sealed goggles Safety glasses according to EN 166 or equivalent **Body protection:** Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved before the product is used by a specialist. If there is a risk of ignition by static electricity, anti-static protective clothing should be worn. For the best protection against static discharge, clothing should consist of anti-static overalls, boots and gloves. For further information on materials and design requirements and test methods consult the European standard EN 1149.

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

| • 9.1 Information on basic physical and chemical pr | operties |
|---|--|
| · Physical state | Liquid |
| Colour: | According to product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| Melting point/freezing point: | Undetermined. |
| Boiling point or initial boiling point and boiling | |
| range | 120.3 °C (107-98-2 1-Methoxy-2-propanol) |
| Flammability | Flammable. |
| Lower and upper explosion limit | |
| Lower: | Not determined. |
| · Upper: | Not determined. |

(Contd. on page 7)

EU

Printing date 06.02.2025

Version: 26 (replaces version 25)

Revision: 06.02.2025

Trade name: ZINKSILICAAT ZL 400-55 PASTA

| | (Contd. of page |
|---|---|
| Flash point: | 35 °C |
| Auto-ignition temperature: | 270 °C (107-98-2 1-Methoxy-2-propanol) |
| Decomposition temperature: | Not determined. |
| рН | Mixture reacts violently with water. |
| Viscosity: | |
| Kinematic viscosity | at 40 °C: > 20,5 mm²/s |
| Dynamic at 20 °C: | 2,200 mPas |
| Solubility | |
| water: | Fully miscible. |
| Partition coefficient n-octanol/water (log value) | Not determined. |
| Vapour pressure: | Not determined. |
| Density and/or relative density | |
| Density at 20 °C: | >3.26 g/cm ³ |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| 9.2 Other information | |
| Appearance: | |
| Form: | Fluid |
| Important information on protection of health and | |
| environment, and on safety. | |
| Ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of |
| | explosive air/vapour mixtures are possible. |
| Solvent content: | |
| Water: | <0.0 % |
| Change in condition | |
| Evaporation rate | Not determined. |
| Information with regard to physical hazard classe | S |
| Explosives | Void |
| Flammable gases | Void |
| Aerosols | Void |
| Oxidising gases | Void |
| Gases under pressure | Void |
| Flammable liquids | Flammable liquid and vapour. |
| Flammable solids | Void |
| Self-reactive substances and mixtures | Void |
| Pyrophoric liquids | Void |
| | |
| Pyrophoric solids | Void |
| Pyrophoric solids Self-heating substances and mixtures | Void Void |
| Self-heating substances and mixtures | |
| Self-heating substances and mixtures Substances and mixtures, which emit flammable | Void |
| Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water | Void Void |
| Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids | Void Void Void |
| Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids Oxidising solids | Void Void Void Void |
| Self-heating substances and mixtures Substances and mixtures, which emit flammable gases in contact with water Oxidising liquids | Void Void Void |

SECTION 10: Stability and reactivity

· 10.1 Reactivity No further relevant information available.

10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.

(Contd. on page 8)

EU

Printing date 06.02.2025

Version: 26 (replaces version 25)

Revision: 06.02.2025

Trade name: ZINKSILICAAT ZL 400-55 PASTA

(Contd. of page 7)

· 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

• 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 • Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

7440-66-6 zinc powder -zinc dust (stabilized)

Oral LD50 >2,000 mg/kg (rat)

107-98-2 1-Methoxy-2-propanol

Oral LD50 5,660 mg/kg (rat)

Dermal LD50 13,000 mg/kg (rabbit)

1314-13-2 Zinc oxide

Oral LD50 >5,000 mg/kg (rat)

1330-20-7 xylene

Oral LD50 3,523 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

Primary irritant effect:

• Skin corrosion/irritation Based on available data, the classification criteria are not met.

• Serious eye damage/irritation Based on available data, the classification criteria are not met.

• Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· Germ cell mutagenicity Based on available data, the classification criteria are not met.

 \cdot Carcinogenicity Based on available data, the classification criteria are not met.

• Reproductive toxicity Based on available data, the classification criteria are not met.

• **STOT-single exposure** Based on available data, the classification criteria are not met.

• STOT-repeated exposure Based on available data, the classification criteria are not met.

• Aspiration hazard Based on available data, the classification criteria are not met. • 11.2 Information on other hazards

Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

· Aquatic toxicity:

| 7440-66-6 zinc | powder -zinc | dust (stabilized) | |
|----------------|--------------|-------------------|--|

LC50/96 h 0.24 mg/l (Oncorhynchus mykiss)

LC50/48 h 0.068 mg/l (Daphnia magna)

0.645-1 mg/l (Penaeus chinensis (fleshy prawn))

107-98-2 1-Methoxy-2-propanol

EC50/48 h 23,300 mg/l (Daphnia magna)

LC50/96 h 6,812 mg/l (Leuciscus idus)

1314-13-2 Zinc oxide

EC50/72 h 0.21 mg/l (algae)

EC50/48 h 0.67 mg/l (Ceriodaphnia dubia)

1330-20-7 xylene

EC50/72 h 2.2 mg/l (algae)

EC50/48 h >3.4 mg/l (Ceriodaphnia dubia)

LC50/96 h 2.6 mg/l (Oncorhynchus mykiss)

LC50/24 h 1 mg/l (Daphnia magna)

12.2 Persistence and degradability No further relevant information available.

• 12.3 Bioaccumulative potential No further relevant information available.

(Contd. on page 9)

EU

Printing date 06.02.2025

Safety data sheet according to Regulation (EC) No 1907/2006, Article 31

Version: 26 (replaces version 25)

Revision: 06.02.2025

(Contd. of page 8)

Trade name: ZINKSILICAAT ZL 400-55 PASTA

· 12.4 Mobility in soil No further relevant information available.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- vPvB: Not applicable.
- 12.6 Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- 12.7 Other adverse effects
- · Remark: Very toxic for fish
- Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Also poisonous for fish and plankton in water bodies.

Very toxic for aquatic organisms

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| · European | · European waste catalogue | |
|------------|---|--|
| 08 00 00 | WASTES FROM THE MANUFACTURE, FORMULATION, SUPPLY AND USE (MFSU) OF COATINGS (PAINTS, VARNISHES AND VITREOUS ENAMELS), ADHESIVES, SEALANTS AND PRINTING INKS | |
| 08 01 00 | wastes from MFSU and removal of paint and varnish | |
| 08 01 11* | waste paint and varnish containing organic solvents or other hazardous substances | |
| HP3 | Flammable | |
| HP14 | Ecotoxic | |

Uncleaned packaging:

- · Recommendation: Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

SECTION 14: Transport information Transport in accordance with ADR/RID, IMDG and ICAO/IATA. 14.1 UN number or ID number · ADR/RID/ADN, IMDG, IATA UN1263 14.2 UN proper shipping name 1263 PAINT, ENVIRONMENTALLY HAZARDOUS · ADR/RID/ADN ·IMDG PAINT, MARINE POLLUTANT · IATA PAINT · 14.3 Transport hazard class(es) · ADR/RID/ADN, IMDG Class 3 Flammable liquids. (Contd. on page 10)

Printing date 06.02.2025

Version: 26 (replaces version 25)

Revision: 06.02.2025

Trade name: ZINKSILICAAT ZL 400-55 PASTA

| | (Contd. of page |
|---|--|
| Label | 3 |
| ΙΑΤΑ | |
| | |
| Class | 3 Flammable liquids. |
| Label | 3 |
| 14.4 Packing group ADR/RID/ADN, IMDG, IATA | III |
| 14.5 Environmental hazards: | |
| Marine pollutant: | Yes |
| | Symbol (fish and tree) |
| Special marking (ADR/RID/ADN): | Symbol (fish and tree) |
| 14.6 Special precautions for user | Warning: Flammable liquids. |
| Hazard identification number (Kemler code): | 30 |
| EMS Number: | F-E, <u>S-E</u> |
| Stowage Category | A |
| 14.7 Maritime transport in bulk according to IM | |
| instruments | Not applicable. |
| Transport/Additional information: | |
| ADR/RID/ADN | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml |
| Transport category | 3 |
| Tunnel restriction code | D/E |
| · IMDG | |
| Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E1 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN 1263 PAINT, 3, III, ENVIRONMENTALLY |
| | HAZARDOUS |

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category
- E1 Hazardous to the Aquatic Environment
- P5c FLAMMABLE LIQUIDS

· Qualifying quantity (tonnes) for the application of lower-tier requirements 100 t

- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 200 t
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

(Contd. on page 11)

EU -

Printing date 06.02.2025

Version: 26 (replaces version 25)

Revision: 06.02.2025

(Contd. of page 10)

3

3

Trade name: ZINKSILICAAT ZL 400-55 PASTA

· REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

108-88-3 toluene

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

108-88-3 toluene

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

· Contact: J. Dijkstra

· Date of previous version: 20.04.2023

Version number of previous version: 25

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances

- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- Flam. Liq. 3: Flammable liquids Category 3

Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Sources

- ECHA European Chemical Agency - http://echa.europa.eu/information-on-chemicals

- SDS of raw materials supplied by producer/supplier.
- ** Data compared to the previous version altered.

FU